


	HUB USB 3.0 CT2U3-13AB-EU-WH-BP 1 m	ACCESS CONTROLLER PR312EM-BK-G ROGER	SMART ACTION TRIGGER ACTIONBOX/BLEBOX Wi-Fi, 230 V AC
			
	152.10 PLN 152.10 PLN	530.00 PLN 530.00 PLN	103.25 PLN 103.25 PLN
Cards support	...	Unique EM 125kHz	...
Application	controlling devices, triggering actions
Reading distance of prox-keys	...	max. 15 cm	...
Rated voltage	230 V AC
Keyboard built-in	...	—	...
Maximal total load	—
Total maximal current	—
Number of inputs	4
Communication	...	<ul style="list-style-type: none"> • RS-485 • RACS (Roger) • Biometric Reader support (RFT1000 Mode) 	...
Number of outputs	0
Connectors	<ul style="list-style-type: none"> • 1 x Socket - USB-B 3.0 • 13 x socket - USB-A • 1 x Power socket - 5.5/2.1 socket
Connector type	screw terminals
Length of the cable	1 m
USB standard	3.0
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Selected features of the standalone mode	...	<ul style="list-style-type: none"> • 4000 indexed users, • 32000 events buffer, • Operation with XM-2 I/O extension module (Full Standalone Mode) 	...
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Housing	Plastic	...	Plastic
"Index of Protection"	IP20
Color	Black

Main features	<ul style="list-style-type: none"> • Solid workmanship • LED indication • Each socket has a separate switch 	<ul style="list-style-type: none"> • The ability to add additional reader (bilateral way door control), • 3 programmable input lines NO/NC, • 2 programmable transistor outputs 1A, • Programmable relay output 1.5A/30V, • Any topology of communication bus, • 99 General Purpose Schedules, • 250 access groups, • Possibility to connect the XM-2 type in/out expander, • Integration with an alarm system via in/out line, • Door modes (Normal, Locked, Unlocked and Conditionally Unlocked), • Identification modes (Card or PIN, Card and PIN, Card only, PIN only), • Two users function, dual identification mode and other advanced functions of access control, • System management via WAN/ LAN network, or COM/USB serial port, • Possibility to split the system into subsystems, • Tamper protection (detection of removing from mounting surface and enclosure opening), • LED indication, • Beep signal 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • µWiFi technology support
Power supply	12 V DC / 5 A (included)	10 ... 15 V DC	...
Average current consumption	...	50 mA	...
Operation temp	...	-25 °C ... 60 °C	-20 °C ... 50 °C
Permissible relative humidity	...	10 ... 95 % (non-condensing)	...
Weight	0.191 kg	0.18 kg	0.027 kg
Dimensions	235 x 62 x 28 mm	152.5 x 46 x 23 mm (Standard housing stand) 152.5 x 46 x 35 mm (Thicker housing stand)	35 x 33 x 23 mm
Manufacturer / Brand	ORICO	ROGER	BleBox
Guarantee	2 years	3 years	2 years