




	HOUSING A19-TS-35/OB-4U	IP SPEED DOME CAMERA OUTDOOR IPC6624SR-X33-VF LightHunter - 4 Mpx 4.5 ... 148.5 mm UNIVIEW
		
	344.00 PLN 344.00 PLN	8159.25 PLN 8159.25 PLN
Standard	...	TCP/IP
Width	19 "	...
Height	4 U	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Material	Steel - powder painted	...
Matrix size	...	4 Mpx
Resolution	...	2688 x 1520 - 4 Mpx
Application	RACK 19"	...
Lens	...	4.5 ... 148.5 mm
View angle	...	51 ° ... 2.5 °
Main features	<ul style="list-style-type: none"> • TH-35 rail • Corrosion resistance • Possibility to mount of 24 fuses, 1 S wide • 6-point fixing to the front RACK rails • 6 pcs. of M6 screws with cage nuts included • The enclosure features labeling field 420x20 mm • 10 rubber bushings in the top and bottom part of the enclosure • Mounting plate for a 17Ah/12V battery included 	...
Optical zoom	...	x 33
Digital zoom	...	x 16
Operation temp	-10 °C ... 40 °C	...
Range of IR illumination	...	150 m
Video output	...	✓
Preset rotation speed	...	<ul style="list-style-type: none"> • 300 °/s (horizontal) • 240 °/s (vertical)
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 200 °/s (horizontal) • 0.1 °/s ... 200 °/s (vertical)
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-15 ° ... 90 °
RS-485 interface	...	✓
Number of presets	...	1024
Horizontal scan	...	✓

Route settings	...	16
Image compression method	...	Ultra H.265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	2 / 1
Audio	...	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Main features	...	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Configurable Privacy Zones - 24 • Motion Detection • Tamper signaling • Image rotation and mirror • Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions • Home Position - set the camera to the specified position if no operator activity for a specified dwell time • Overvoltage protection : 6 kV • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, crowd gathering estimation, people counting
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3at), • 24 V DC / 2.5 A (power adapter included), • 24 V AC
Power consumption	...	≤ 25 W
Housing	...	Speed Dome, Metal
Color	Black (RAL 9005)	White
Operation temp	...	-40 °C ... 70 °C
"Index of Protection"	IP20	IP66
Vandal-proof	...	—
Weight	3.73 kg	5.31 kg

Dimensions	<ul style="list-style-type: none"> • 445 x 170 x 155 mm Internal dimensions • 481.5 x 175 x 234 mm External dimensions 	Ø 227 x 385 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	PULSAR	UNIVIEW
Guarantee	2 years	2 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00