



	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H54B - 8.3 Mpx, 4K UHD</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H24M-36 - 1080p 4 mm</a>
		
	424.00 PLN 424.00 PLN	168.00 PLN 168.00 PLN
Standard	AHD, HD-CVI, HD-TVI, PAL	AHD / HD-CVI / HD-TVI / PAL
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS	1/2.8 " Sony CMOS - STARVIS Back-illuminated
Matrix size	8.3 Mpx	2.1 Mpx
View angle	...	<ul style="list-style-type: none"> <li>• 72 ° (manufacturer data)</li> <li>• 80 ° (our tests result)</li> </ul>
Application	...	The camera is designed for indoor use, due to the possibility of steam condensation.
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD / HD-CVI / HD-TVI @ 12.5 fps, 15 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-CVI / HD-TVI, 20 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps , 2560 x 1440 - 4 Mpx @ AHD @ 15 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps , 960 x 576 - 960H @ CVBS	<ul style="list-style-type: none"> <li>• 1920 x 1080 - 1080p, AHD / HD-CVI / HD-TVI,</li> <li>• 1280 x 720 - 720p / AHD / HD-CVI / HD-TVI,</li> <li>• 960 x 576 - 960H, PAL</li> </ul>
Video output	1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI, PAL - selectable by buttons	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL
Lens	—	4 mm
Auto Iris socket	DC	...
Min. illumination	0.001 Lux @ F1.2	0.001 Lux
IR illuminator support	ICR - Movable InfraRed filter	...
Audio	—	—
Alarm inputs / outputs	—	...
RS-485 interface	—	...
OSD menu	✓	✓

Main features	<ul style="list-style-type: none"> <li>• WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC - configurable Back Light Compensation</li> <li>• White Balance - ATW/Manual</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> </ul>
Power supply	12 V DC / 150 mA	12 V DC / 120 mA
Power consumption	≤ 1.8 W	...
Housing	BOX, Metal	Mini, Metal
Color	White + Black	Black
Operation temp	-20 °C ... 60 °C	-10 °C ... 50 °C
Weight	0.54 kg	0.03 kg
Dimensions	149 x 82 x 58 mm	30 x 30 x 29 mm (without bracket)
Supported languages	English, Spanish, Portuguese	Polish, English, French, Spanish, Japanese, Portuguese, Russian, Italian
Manufacturer / Brand	APTI	APTI
Guarantee	2 years	2 years