

| | | |
|-----------------------|---|---|
| | LED FLOODLIGHT WITH MOTION SENSOR OR-NL-348BLPPR4 ORNO | ACCESS POINT U6-MESH Wi-Fi 6, 2.4 GHz, 5 GHz, 573.5 Mbps + 4800 Mbps UBIQUITI |
| |  |  |
| | 199.06 PLN 199.06 PLN | 1074.29 PLN 1074.29 PLN |
| Luminous flux | 1500 lm | ... |
| Light color | Neutral, 4000 K | ... |
| Frequency range | ... | 2.4 GHz, 5 GHz , |
| Twilight switch | ✓ | ... |
| Nominal power | 25 W | ... |
| CRI | > 85 | ... |
| Antenna type | ... | <ul style="list-style-type: none"> • 2x2 UL MU-MIMO @ 2.4 GHz - 3 dBi, • 4x4 UL/DL MU-MIMO @ 5 GHz - 5 dBi Integrated - Omnidirectional antenna |
| Standards | ... | <ul style="list-style-type: none"> • IEEE 802.11 a/b/g/n/ac/ax, • IEEE 802.1Q VLAN |
| Baud rates | ... | 573.5 Mbps @ 2.4 GHz + 4800 Mbps @ 5 GHz |
| Protections | ... | WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3) |
| LAN ports | ... | 1 x 10/100/1000 Mbps |
| Transmitter power | ... | <ul style="list-style-type: none"> • 22 dBm @ 2.4 GHz (max) • 26 dBm @ 5 GHz (max) |
| Power supply PoE | ... | Ubiquiti Passive PoE |
| Housing | Aluminum / Plastic (polycarbonate) | ... |
| "Index of Protection" | IP44 | ... |
| Power supply | 230 V AC | <ul style="list-style-type: none"> • 44 ... 57 V DC PoE, • 48 V / 0.32 A - PoE Adapter (included) |
| Power consumption | ... | 11.4 W |

| | | |
|-------------------------------|---|---|
| Main features | <ul style="list-style-type: none"> • 10 x LED SMD diodes • LED lifetime 50 000 h • Solid workmanship • PIR detector - Built-in, Range : 12 m, Detection angle : 180 °, Motion Detection : 0.6 ... 1.5 m/s • Sensitivity adjustment of the twilight sensor • Lighting time adjustment : 10 ... 420 s • Tilt adjustment <ul style="list-style-type: none"> - Twilight Sensor : 180 ° (horizontal), 90 ° (vertical) - LED Floodlight : 45 ° (horizontal), 135 ° (vertical) | <ul style="list-style-type: none"> • Easy to install on any wall or pole • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • Support for WiFi4/WiFi5/WiFi6 • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Guest Network - a separate and secure network for guests • QoS - Rate limit • > 300 on-line users • Bluetooth interface • "Index of Protection" : IPX5 |
| Operation temp | -20 °C ... 40 °C | -30 °C ... 60 °C |
| Permissible relative humidity | ... | 5 % ... 95 % |
| Weight | 1.22 kg | <ul style="list-style-type: none"> • 0.41 kg • 0.44 kg (with mounting kits) |
| Dimensions | 180 x 208 x 178 mm | Ø 49 x 160 mm |
| Manufacturer / Brand | ORNO | UBIQUITI |
| Guarantee | 2 years | 2 years |