



	NVR NVR608RH-32-XI 32 CHANNELS WizMind DAHUA	MAGNET IN A HERMETIC ENCLOSURE OPXM-1-GY SATEL
		
	21787.00 PLN 21787.00 PLN	37.00 PLN 37.00 PLN
Standard	IP	...
Support	...	AXD-200, XD-2
Supported resolutions	max. 32 Mpx	...
"Index of Protection"	...	IP65
Color	...	Gray
Video outputs	<ul style="list-style-type: none"> • 2 pcs HDMI 4K • 1 pcs HDMI 8K • 1 pcs HDMI • 2 pcs VGA 	...
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras, • Bi-directional audio streaming support 	...
Audio inputs	1 pcs CINCH	...
Audio outputs	2 pcs CINCH	...
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MPEG-4 / MJPEG	...
Bitrate	max. 1280 Mbps	...
Supported hard drives	8 x 16 TB SATA + 1 x eSATA , Raid 0/1/5/6/10	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Records playback from max. 16 channels in the same time 	...
Network interface	2 x RJ-45 10/100/1000/2500 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...
ONVIF	✓	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	...
Web browser access ports	80, 37777	...

PC client access ports	37777	...
Mobile client access ports	37777	...
RTSP URL	<ul style="list-style-type: none"> • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	...
USB	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 2 pcs USB 3.0 	...
Serial ports	RS-485, RS-232	...
Alarm inputs / outputs	16 / 8	...
PTZ control	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others 	...
Intelligent image analysis	✓	...
Motion Detection	✓	...
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : IVS analysis - 10 rules, scene changing, face detection, • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Face recognition - supports 6 types of facial attributes extraction • Face recognition and analysis in real time (up to 16 photos per second) • Support for up to 40 face databases, including 300 000 face images • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) • AcuPick support - technology that uses artificial intelligence on both front-end and back-end to search through massive amounts of video data to quickly locate targets with high precision • EPTZ - advanced target detection and tracking algorithms that trigger alarms - can simultaneously zoom and track many people and/or vehicles <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map 	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	<ul style="list-style-type: none"> • 100 ... 240 V AC @ 50 / 60 Hz • Redundant power supply 	...
Power consumption	max. 18 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	8.14 kg	0.05 kg
Dimensions	444 x 476 x 95 mm	102 x 23 x 20 mm



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	Polish, English	...
Manufacturer / Brand	DAHUA	SATEL
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00