




	IP VANDALPROOF CAMERA IPC2328SB-DZK-I0 - 8.3 Mpx 2.8 ... 12 mm - MOTOZOOM UNIVIEW	MAINS ADAPTER WITH GROUNDING WS-PL/GS- UNI-3
		
	2554.20 PLN 2554.20 PLN	6.68 PLN 6.68 PLN
Standard	TCP/IP	...
Voltage	...	250 V AC
Sensor	1/2.8 " Progressive Scan CMOS	...
Max. current	...	10 A
Matrix size	8.3 Mpx	...
Material	...	PVC
Main features	...	Color : White
Resolution	3840 x 2160 - 8.3 Mpx , 3072 x 1728 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p	...
Lens	2.8 ... 12 mm - Motozoom, AutoFocus	...
View angle	• 107 ° ... 29 ° (manufacturer data) • 100 ° ... 30 ° (our tests result)	...
Range of IR illumination	50 m	...
S/N ratio	> 52 dB	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	• External microphone input, • Audio output, • Audio transmission via network, • Audio detection	...
Main stream frame rate	20 fps @ 8.3 Mpx 25 fps @ 5 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, IEEE 802.1x, QoS, SSL / TLS, SSH	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...

Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 880 mA 	...
Power consumption	≤ 10.5 W	...
Housing	Compact, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.91 kg	...

Dimensions	245 x 86 x 72 mm	55 x 55 x 46 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00