





	WIRELESS OUTDOOR SIREN JA-163A-BASE JABLOTRON	SWITCHING ADAPTER DRL-24V240W-1EN LYTE II Delta Electronics	AHD, HD-CVI, HD-TVI, CVBS CAMERA APTI-H52V31-2812W - 8.3 Mpx 4K UHD 2.8 ... 12 mm
			
		287.18 PLN 287.18 PLN	248.00 PLN 248.00 PLN
Support	JABLOTRON 100
Adapter type	...	Switching	...
Sound pressure level	110 dB
Frequency bandwidth of the system	868.1 MHz
Power voltage	...	90 ... 264 V AC	...
Radio communication range (at open area)	max. 300 m
Output voltage	...	24 V DC	...
Standard	AHD, HD-CVI, HD-TVI, CVBS
Sensor	1/2.5 " Sony CMOS
Matrix size	8.3 Mpx
Output voltage adjustment	...	21.6 ... 26.4 V DC	...
Maximal load	...	10 A	...
Output power	...	240 W	...
Number of outputs	...	2 pcs	...
Efficiency	...	90 %	...
Housing type	...	DIN	...
Internal backup battery	—
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage • Temperature 	...
Operation temp	-25 °C ... 60 °C
Operation temp. / Relative humidity	...	-40 °C ... 70 °C / 20 ... 95 %	...

Resolution	<ul style="list-style-type: none"> • 3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI @ 12.5 fps, 15 fps • 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 12.5 fps, 20 fps, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 15 fps, 25 fps, 30 fps, • 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps, • 960 x 576 - 960H @ PAL
Range of IR illumination	30 m
IR illuminator power adjustment	Automatic
Lens	2.8 ... 12 mm
View angle	<ul style="list-style-type: none"> • 92 ° ... 27 ° (manufacturer data) • 94 ° ... 37 ° (our tests result)
S/N ratio	≥ 50 dB
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch
Main features	<ul style="list-style-type: none"> • Tamper protection (detection of removing from mounting surface and enclosure opening) • Battery lifetime max. 5 years 	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines
OSD menu	✓
Vandal-proof	—
"Index of Protection"	IP66
Power supply	3.6 V DC / 13 Ah - Lithium battery BAT-100 (not included) - 1 or 2 pcs	...	12 V DC / 390 mA
Power consumption	≤ 4.7 W
Housing	Dome - Metal
Color	Gray	...	White
Operation temp	-20 °C ... 50 °C
Weight	0.43 kg	0.62 kg	0.56 kg
Dimensions	292 x 189 x 44 mm	123.6 x 116.8 x 40 mm	Ø 120 x 83 mm

Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	JABLOTRON	Delta Electronics	APTI
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00