



	INSULATION RESISTANCE METER + RCD TESTER UT-526 UNI-T	CABLE USB-W-C/USB-W-1M/B 1.0 m
		
	890.13 PLN 890.13 PLN	9.12 PLN 9.12 PLN
Cable	...	USB-C plug / USB-A plug
Material	...	PVC
Length of the cable	...	1.0 m
Color	...	Black
USB standard	...	2.0
Resistance measurement	<ul style="list-style-type: none"> • Test voltage 250 V : 0.05 MΩ ... 200 MΩ • Test voltage 500 V : 0.05 MΩ ... 300 MΩ • Test voltage 1000 V : 0.05 MΩ ... 500 MΩ 	...
Cable diameter	...	~ 3 mm
Measuring accuracy	0.05 MΩ ... 500 MΩ ± (5% + 5)	...
Open circuit voltage	Test voltage + 10 %	...
Test current	0.9 mA ... 1.1 mA	...
Short-circuit current	< 1.8 mA	...
AC voltage measurement	0 V ... 440 V ± (2% + 3) @ 1 V	...
DC voltage measurement	0 V ... 440 V ± (2% + 3) @ 1 V	...
Measurement of small resistances	0.01 Ω ... 2000 Ω ± (2% + 5)	...
Frequency measurement	20 Hz ... 100 Hz - for reference only	...
Test of RCDs	<ul style="list-style-type: none"> • Working voltage: 220V ± 10 % • Test current: 10mA / 30mA / 100mA / 300mA • Switch-off time ranges : <ul style="list-style-type: none"> - 0 ... 2000 ms ± (5% + 2) @ 10 mA <ul style="list-style-type: none"> - 0 ... 500 ms ± (5% + 2) @ 30 mA <ul style="list-style-type: none"> - 0 ... 300 ms ± (5% + 2) @ 100 mA <ul style="list-style-type: none"> - 0 ... 300 ms ± (5% + 2) @ 300 mA	...

Automatic change of measuring ranges	—	...
RS-232	—	...
USB	—	...
Main features	<ul style="list-style-type: none"> • Warning of using high voltage during the measurement, • Phase switch 0° / 180° during RCD test, • Automatic identification of AC/DC voltage, • Large, readable LCD display with backlight, • Buzzer, • Low battery level alarm, • Aesthetic and solid construction 	<ul style="list-style-type: none"> • High noise immunity • 100% copper conductor • 2 x Cu - AWG 30 : Data + 2 x Cu - AWG 24 : Power supply • Solid workmanship
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	≤ 85 % (non-condensing)	...
Power supply	6 x 1.5V, type AA/LR6/FR6 battery - included	...
Weight	0.45 kg	0.023 kg
Dimensions	150 x 100 x 71 mm	...
Manufacturer / Brand	UNI-T	...
Guarantee	2 years	2 years