


	IP CAMERA BCS-L-EIP55FCR3L3-AU-G(2) - 5 Mpx 2.8 mm BCS Line	IP CAMERA IPC-HFW1530S-0280B-S6-BLACK 5 Mpx 2.8 mm DAHUA
	1589.00 PLN 1589.00 PLN	794.00 PLN 794.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Matrix size	5 Mpx	5 Mpx
Resolution	2960 x 1688 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3.1 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	• 97 ° (manufacturer data) • 104 ° (our tests result)	• 106 ° (manufacturer data) • 101 ° (our tests result)
Range of IR illumination	30 m	30 m
RS-485 interface	—	—
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	—
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding	H.265+ / H.265 / H.264 / H.264+ / MJPEG
Alarm inputs / outputs	1 / 1	—
Audio	• Microphone built-in • Audio transmission via network • Compliance with the AAC standard	• Microphone built-in • Audio transmission via network • Audio detection
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, DDNS, NTP, Multicast
WEB Server	Built-in	Built-in
Max. number of on-line users	20	6
ONVIF	21.12	20.06
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	192.168.1.108	192.168.1.108
Main stream frame rate	25 fps @ 8.3 Mpx	20 fps @ 5 Mpx 25 fps @ 4 Mpx
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777	80, 37777
PC client access ports	37777	37777
Mobile client access ports	37777	37777
Port ONVIF	80	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Motozoom lens - Controlling from browser, NVR or software • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • Audio detection • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable Privacy Zones • Audio detection • Mirror - Mirror image
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 730 mA 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 330 mA
Power consumption	≤ 8.8 W	<ul style="list-style-type: none"> • ≤ 3,9 W @ 12 V DC • ≤ 4,5 W @ PoE (802.3af)
Vandal-proof	—	...
Housing	Dome - Metal	Compact - Metal
Color	Graphite	Black
"Index of Protection"	IP67	IP67
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.75 kg	0.32 kg
Dimensions	Ø 122 x 108 mm	Ø 70 x 162 mm
Supported languages	Polish, English	English, Spanish, Russian
Manufacturer / Brand	BCS Line	DAHUA
Guarantee	3 years	3 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00