



| | OPENING DETECTOR WITH AUDIO SIGNAL MA-05A3 | ALARM KIT WAS-90H1 EL HOME |
|--------------------------------------|---|--|
| |  |  |
| | 17.73 PLN 17.73 PLN | 202.73 PLN 202.73 PLN |
| Number of supported wireless devices | ... | max. 16 pcs |
| PIR detectors included | ... | 2 pcs, Wireless |
| Magnetic contact included | ... | 1 pcs, Wireless |
| Enclosure included | ... | ✓ |
| Keyboard included | ... | — |
| Expander included | ... | — |
| Battery power supply | Battery 3 x 1.5 V LR44 included | ... |
| Wireless | ... | 433.93 MHz |
| Operating range in open area | ... | max. 50 m |
| Access from PC | ... | — |
| Mobile phones support | ... | <ul style="list-style-type: none"> • Android: Free application eWeLink, • iOS (iPhone): Free application eWeLink |
| Main features | ... | <ul style="list-style-type: none"> • Built-in module to support wireless devices operating in the 433 MHz frequency band, • Built-in Wi-Fi module 2.4 GHz IEEE 802.11 b/g/n, • Phone notification - Signal to the eWeLink mobile application, • Configuration is done using the mobile application • LED indication |
| Power supply | ... | <ul style="list-style-type: none"> • 5 V micro USB connector • 5 V DC / 2 A (power adapter included) |
| Detection | Opening the door or window | Opening the door or window |
| Alarm inputs | ... | — |
| Application | ... | Indoor |
| Sensor type | ... | Passive Infra Red (PIR) |
| Frequency range | ... | 433.93 MHz 433.93 MHz |

| | | |
|--|--|---|
| Radio communication range (at open area) | ... | max. 50 m max. 50 m |
| Recommended installation height | ... | 2.0 ... 2.4 m |
| Detection range / Detection angle | ... | 12 m / 110 ° |
| Sensitivity adjustment | ... | — |
| Pet immunity | ... | < 20 kg |
| Digital temperature compensation | ... | — |
| Alarm signaling | <ul style="list-style-type: none"> • Alarm siren max. 105 dB, • Beep signal - Entry signaling device | Signal to the eWeLink mobile application - via RB-80H1 Signal to the eWeLink mobile application - via RB-80H1 |
| Main features | Turning by switch | LED indicator |
| Housing | ... | Plastic Plastic Plastic |
| Color | ... | Black White White |
| "Index of Protection" | IP20 | IP20 IP20 IP20 |
| Battery | ... | 1 x A23 12 V (not included) 2 x LR3 (AAA) 1.5 V (not included) |
| Current consumption | ... | ≤ 15 mA (Standby mode) ≤ 40 mA (operation) ≤ 5 μA (Standby mode) ≤ 15 mA (operation) ≤ 9 μA (Standby mode) ≤ 10 mA (operation) |
| Operation temp | 10 °C ... 40 °C | 0 °C ... 40 °C 0 °C ... 40 °C 0 °C ... 40 °C |
| Weight | 0.042 kg | 0.04 kg <ul style="list-style-type: none"> • 0.020 kg - Transmitter • 0.007 kg - Magnet 0.062 kg |

| | | |
|----------------------|---|---|
| Dimensions | <ul style="list-style-type: none"> • Transmitter : 32 x 65 x 24 mm • magnet : 10 x 53 x 15 mm | 62 x 62 x 20 mm <ul style="list-style-type: none"> • 70 x 31 x 19 mm - Transmitter • 42 x 14 x 16 mm - Magnet 105 x 58 x 43 mm |
| Manufacturer / Brand | EURA | EL HOME |
| Guarantee | 2 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00