

	TV OR MONITOR MOUNT BRATECK-KL21G-46T	IP CAMERA IPC-PDW3849-A180-E2-AS-PV-0280B PANORAMIC TiOC Full-Color - 7.6 Mpx 2 X 2.8 mm DAHUA
		
	29.30 PLN 29.30 PLN	2209.00 PLN 2209.00 PLN
Standard	...	TCP/IP
Sensor	...	2 x 1/2.8 " Progressive Scan CMOS
Matrix size	...	2 x 4 Mpx
Mounting standard	VESA : 100, 200 x 100, 200, 300, 400 x 200, 400, 600 x 400	...
Screen size range	37 " ... 70 "	...
Bearing capacity	40 kg	...
Distance from mounting surface	53 mm	...
Tilt adjustment	-12 ° ... 12 °	...
Horizontal rotation	—	...
Rotation in the plane of the screen	—	...
Resolution	...	4096 x 1860 - 7.6 Mpx , 3632 x 1632 - 6 Mpx , 3040 x 1368 - 4.1 Mpx , 1200 x 530 - 0.6 Mpx , 1920 x 860 - 1.6 Mpx , 960 x 432 - 0.4 Mpx
Lens	...	2 x 2.8 mm
View angle	...	• 180 ° (manufacturer data) • 180 ° (our tests result)
Range of IR illumination	...	25 m
White light LED illuminator range	...	20 m
Min. illumination	...	0.005 Lux / F1.0 (color)
S/N ratio	...	> 56 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	AI H.265 / H.265+ / AI H.264 / H.264+
Alarm inputs / outputs	...	1 / 1
Audio	...	• Microphone built-in, • External microphone input, • Speaker built-in • Audio output • Bi-directional audio streaming support • Audio detection • Compliance with the AAC standard
Main stream frame rate	...	20 fps @ 7.6 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	...	20
ONVIF	...	22.12
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	• Active deterrence function, Alternately flashing LEDs: red and blue - frequency configuration, Siren sound - 3 volume levels • EPTZ - advanced target detection and tracking algorithms that trigger alarms - can simultaneously zoom and track many people and/or vehicles • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles • SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms • AI SSA AI Smart Scene Adaptive - scene auto-adaptation using deep learning algorithms to detect environmental conditions such as rain, fog, backlight, low light and flickering, in order to set the optimal image parameters • BLC/HLC - Back Light / High Light Compensation • Day/night mode • Full Color - colorful night mode • Auto White Balance • AGC - Automatic Gain Control • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Mirror - Mirror image • Light and sound alarm • White light (LED) illuminator built-in : 2 LEDs • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, video tampering, Audio detection
Power supply	...	• PoE (802.3af), • 12 V DC / 750 mA



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power consumption	...	• ≤ 10.3 W @ PoE • ≤ 9 W @ 12 V
Housing	...	Dome - Metal
Color	Black	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	1.74 kg	0.97 kg
Dimensions	643 x 425 x 53 mm	Ø 122 x 132 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian
Manufacturer / Brand	BRATECK	DAHUA
Guarantee	2 years	5 years

