



	COAXIAL CABLE TRI-LAN-400 50 Ω	RFID PROXIMITY CARD ATLO-104S*P200
		
	11.60 PLN 11.60 PLN	152.00 PLN 152.00 PLN
In package	...	200 pcs The price for package
In section	100 m . Price for 1m when buying a whole roll	...
Standard	...	Unique EM 125kHz
Compatibility	...	EM4100/4102
Possibility of programming the serial number (ID)	...	—
Inner conductor	Ø 2.7 mm Cu ± 0.02 mm Wire	...
Ability to write to internal memory	...	—
Serial Number overprint	...	✓
Dielectric	Ø 7.2 mm Physical foam	...
Shield	Foil - Al/PET	...
Braid	168 x Ø 0.15 mm Stranded wire CuSn	...
Impedance	50 Ω	...
Weight	...	0.006 kg
Outer coating	Ø 10.3 mm ± 0.20 mm PE	...
Dimensions	...	86 x 54 x 1 mm
Manufacturer / Brand	...	ATLO
Main features	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C 	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A • Range : ~ 11 cm • The TK-4100 chip

Cable attenuation at 100m section	Temperature : 20 °C 2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz	...
Maximum transmitted power	3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz	...
Guarantee	2 years	2 years

