





	ACCESS POINT 4G+ LTE +ROUTER RUT260 2.4 GHz 300 Mbps Teltonika	POLE MOUNT BCS-V-AS BCS View	SWITCH POE GTX-A1-10-82 8-PORT	RJ-45 PLUG INTERNAL SHIELD RJ45/WP-Y/IN
				
	709.50 PLN 709.50 PLN	227.00 PLN 227.00 PLN	270.40 PLN 270.40 PLN	0.15 PLN 0.15 PLN
Suitable for cameras	...	BCS View
Frequency range	2.4 GHz
Application	RJ-45 modular plug internal shield
Pole diameters range	...	Ø 67 ... Ø 127 mm
Material	...	Stainless steel	...	Plastic
Antenna type	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Color	...	White	...	Yellow
Standards	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G
Management	—	...
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act	...
LAN ports	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN	...	• 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink	...
Transmission speed	10 / 100 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	...
Transmitter power	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA
Operation modes	• N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps	...
LED indicators	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator

Maximal output power	• 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports	...
Maximal total power	120 W	...
Network type	4G, 3G
MAC addresses table	1k	...
Certificates	CE, FCC Class B	...
LTE	✓
QSS	—
WDS	—
DHCP server	✓
Protections	<ul style="list-style-type: none"> • WPA3-EAP • WPA3-SAE • WPA2-Enterprise - PEAP • WPA2-PSK • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering 	...	Overvoltage ± 4 kV	...
Management interface	Web browser, Teltonika RMS application, SMS
Main features	<ul style="list-style-type: none"> • Support for IoT (Internet of Things) systems, • Ability to work as a Hotspot, • Support for VoIP technology, • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems 	...	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	...
Power supply	<ul style="list-style-type: none"> • 9 V DC / 1 A (power adapter included) • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1 	...	100 ... 265 V AC	...
Power consumption	≤ 6.5 W
Operation temp	-40 °C ... 75 °C	...	-10 °C ... 45 °C	...
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.13 kg	1.5 kg	0.76 kg	0.0005 kg
Dimensions	83 x 80 x 25 mm	127 x 250 x 46 mm	210 x 150 x 35 mm	20.3 x 11.7 x 7.9 mm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	Teltonika	BCS View
Guarantee	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00