



	CONNECTOR STRIP WAGO-2273-208*P50	GUARD STATION VTS5A40B DAHUA
		
	96.26 PLN 96.26 PLN	3984.00 PLN 3984.00 PLN
Compatibility	...	The SIP Systems
Shield	...	10 " TFT-LCD color matrix
Resolution	...	1024 x 600
In package	50 pcs The price for package	...
Number of terminal pairs	1	...
Connector type	8 x spring terminal	...
Wire gauge	0.5 ... 2.5 mm ² - Wire	...
Nominal voltage	450 V	...
Rated current	24 A	...
Main features	...	<ul style="list-style-type: none"> • Microphone built-in, • Speakers built-in, • A handset with a microphone that can be used interchangeably with the hands-free mode, • The Hirose 4-pin connector for connecting an external microphone, • 1 x USB 2.0 + 1 x USB 3.0, • 1 x HDMI - Video output, max. 1024 x 600 px, • Bidirectional communication - Audio, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • IP Dahua cameras support, • Noise and echo reduction, • The ability of direct communication between two or more panels, • Micro SD memory cards up to 512GB support (possible local recording), • Port RS-485, • Network interface: LAN - 100/1000 Base-T, • Cooperation with the SIP server
Controlling	...	One-touch action buttons + capacitive touch screen

Default administrator password	...	The administrator password should be set at the first start
Default user password	...	123456
Alarm inputs	...	4 pcs
Relay outputs	...	1 pcs NO
Power supply	...	12 V DC / 4 A (power adapter included) ,
Color	Light gray	Graphite
Operation temp	...	-10 °C ... 55 °C
Weight	...	1.64 kg
Dimensions	18 x 16.7 x 10.4 mm	345 x 225 x 28 mm
Supported languages	...	English
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years