

	<a href="#">COUPLER HDMI-GG</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500TLM-IL-A-0280B-S2 - 5 Mpx 2.8 mm DAHUA</a>	<a href="#">ACCESS POINT 4G LTE +ROUTER RUT200 2.4 GHz 300 Mbps Teltonika</a>
			
	4.40 PLN 4.40 PLN	388.00 PLN 388.00 PLN	425.70 PLN 425.70 PLN
Frequency range	...	...	2.4 GHz
Standard	...	AHD, HD-CVI, HD-TVI, CVBS	...
Connector type	Coupler HDMI Socket / HDMI Socket	...	...
Antenna type	...	...	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Standards	...	...	IEEE 802.11 b/g/n, 4G LTE, 3G, 2G
Baud rates	...	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.234 Mbps (4G / 3G / 2G)
LAN ports	...	...	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN
Resolution	...	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 4 Mpx @ HD-CVI / HD-TVI / AHD @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	...
Sensor	...	Progressive Scan CMOS	...
Lens	...	2.8 mm	...
View angle	...	106 °	...
Range of IR illumination	...	40 m	...
White light LED illuminator range	...	40 m	...
IR illuminator power adjustment	...	Automatic	...
Transmitter power	...	...	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM

Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
LED indicators	...	...	Power, WAN, WLAN, LAN, LTE (4G / 3G / 2G), Signal indicator
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio support via coaxial cable - HD-CVI only</li> </ul>	...
OSD menu	...	✓	...
Network type	...	...	4G, 3G, 2G
Main features	...	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
Housing	...	Compact Plastic + Metal	...
LTE	...	...	✓
Color	...	White + Black	...
QSS	...	...	—
"Index of Protection"	...	IP67	...
Mechanical protection class	...	—	...
WDS	...	...	—
DHCP server	...	...	✓
Operation temp	...	-40 °C ... 60 °C	...
Protections	...	...	<ul style="list-style-type: none"> <li>• WPA2-Enterprise - PEAP</li> <li>• WPA-PSK/WPA2-PSK</li> <li>• WPA-EAP</li> <li>• AES-CCMP</li> <li>• WEP</li> <li>• TKIP</li> <li>• Auto Cipher modes</li> <li>• Client separation</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>
Management interface	...	...	Web browser, Teltonika RMS application, SMS

Main features	...	...	<ul style="list-style-type: none"> <li>• SIM socket</li> <li>• DHCP Relay support</li> <li>• DHCP client list</li> <li>• Static / dynamic routing</li> <li>• VPN support</li> <li>• Default address : 192.168.1.1</li> <li>• Configuration using the Teltonika RMS application</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> </ul>
Power supply	...	12 V DC / 380 mA	<ul style="list-style-type: none"> <li>• 9 V DC / 1 A (power adapter included)</li> <li>• 9 ... 30 V DC</li> <li>• 9 ... 30 V DC - Passive PoE, Powering from LAN1</li> </ul>
Power consumption	...	≤ 4.5 W	≤ 6.5 W
Operation temp	...	...	-40 °C ... 75 °C
Permissible relative humidity	...	...	10 % ... 90 % (non-condensing)
Weight	0.01 kg	0.3 kg	0.13 kg
Dimensions	30 x 23 x 12 mm	198 x 80 x 76 mm	83 x 80 x 25 mm
Manufacturer / Brand	...	DAHUA	Teltonika
Guarantee	2 years	3 years	2 years