

	NVR NVR616DH-128-XI 128 CHANNELS WizMind DAHUA	LED AMPLIFIER AMPBOX/BLEBOX 12 ... 24 V DC
		
	8527.04 GBP 8527.04 GBP	14.65 GBP 14.65 GBP
Standard	IP	...
Supported resolutions	max. 32 Mpx	...
Video outputs	<ul style="list-style-type: none"> • 2 pcs HDMI 4K • 1 pcs HDMI 8K • 1 pcs HDMI • 2 pcs VGA 	...
Application	...	<ul style="list-style-type: none"> • Works with LED controllers : WLIGHTBOX-V3/BLEBOX, WLIGHTBOX-S-V2/BLEBOX, REFLECTIVE-SWITCH/BLEBOX, TWILIGHT-SWITCH/BLEBOX, PROXIDIMMER/BLEBOX, • Works with LED lighting - (RGB/RGBW/CCT/MONO) 12-24V LED strips
Rated voltage	...	12 ... 24 V DC
Audio support	<ul style="list-style-type: none"> • 128 Channels - Audio from cameras, • Bi-directional audio streaming support • Audio detection 	...
Maximal total load	...	480 W
Audio inputs	1 pcs CINCH	...
Audio outputs	2 pcs CINCH	...
Total maximal current	...	20 A (5 A / Channel)
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264	...
Number of inputs	...	4
Bitrate	max. 1280 Mbps	...
Number of outputs	...	4
Connector type	...	screw terminals
Wireless	...	—
Supported hard drives	16 x 20 TB SATA + 1 x eSATA , Raid 0/1/5/6/10	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 16 channels in the same time 	...
Network interface	4 x RJ-45 10/100/1000/2500 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

ONVIF	22.06	...
Default IP address	192.168.1.108	...
Main features	...	<ul style="list-style-type: none"> • High power - max. 480 W, • Digital signal enhancement, • Signal correction : digital, • Protections : optical isolation, • Powerful and high performance, • Small dimensions
Housing	...	Plastic
Default admin user / password	admin / - The administrator password should be set at the first start	...
"Index of Protection"	...	IP20
Color	...	Black
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	—
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
RTSP URL	<ul style="list-style-type: none"> • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	...
USB	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 2 pcs USB 3.0 	...
Serial ports	<ul style="list-style-type: none"> • 2 pcs RS-485 • 1 pcs RS-232 	...
Alarm inputs / outputs	32 / 16	...
PTZ control	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others 	...
Intelligent image analysis	✓	...
Motion Detection	✓	...



Main features	<ul style="list-style-type: none"> • Panel with LCD display, • Intelligent image analysis : IVS analysis - 10 rules, scene changing, face detection, • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Face recognition - supports 6 types of facial attributes extraction • Face recognition and analysis in real time (up to 16 photos per second) • Support for up to 40 face databases, including 300 000 face images • metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) • AcuPick support - technology that uses artificial intelligence on both front-end and back-end to search through massive amounts of video data to quickly locate targets with high precision • EPTZ - advanced target detection and tracking algorithms that trigger alarms - can simultaneously zoom and track many people and/or vehicles <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • Authorized and unauthorized license plate lists: up to 20 000 records • counting people / vehicles • crowd gathering estimation • heat map 	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	100 ... 240 V AC @ 50 ± 2 Hz	...
Power consumption	max. 25 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	-20 °C ... 50 °C
Weight	12.83 kg	0.036 kg
Dimensions	485 x 522 x 133 mm	48 x 39 x 18 mm
Supported languages	Polish, English	...
Manufacturer / Brand	DAHUA	BleBox
Guarantee	3 years	2 years