



	<a href="#">TIME &amp; ATTENDANCE RECORDER ASA1222G DAHUA</a>	<a href="#">CONNECTION BOX PUH-3PK</a>
		
	929.00 PLN 929.00 PLN	23.98 PLN 23.98 PLN
Number of intakes	...	2
Identification time	< 1.5 s	...
"Index of Protection"	...	IP66
FAR (False Acceptance Rate)	≤ 0.00004 %	...
Voltage insulation	...	450 V
FRR (False Rejection Rate)	≤ 0.15 %	...
Cable diameter	...	Ø 4 ... Ø 9 mm
Cards support	13.56 MHz S50	...
Reading distance of prox-keys	1 ... 3 cm	...
Keyboard built-in	✓	...
Autonomous operation	✓	...
Internal dimensions	...	70 x 44 x 29 mm - From the 70 mm dimension, the thickness of the gland nuts should be subtracted, which enter the box to a depth of 5 mm each
Doorbell button	—	...
Communication	• TCP/IP, • USB - The ability to firmware upgrade	...
Relay output	1 x NO/NC	...
Internal memory	8 MB	...
Memory card slot	—	...
Number of supported readers	—	...
Default admin user / password	admin / admin	...

Main features	<ul style="list-style-type: none"> <li>• Full support via network</li> <li>• Possibility of integration with systems based on SmartPSS software,</li> <li>• 1000 indexed users,</li> <li>• 2000 indexed fingerprints (maximum 3 per user),</li> <li>• Possibility to program up to 1000 user cards,</li> <li>• Non-volatile log buffer of the last 100 000 events,</li> <li>• LCD display - 2.4 ",</li> <li>• Sound signaling</li> <li>• Software update via network</li> <li>• It is possible to connect the door release button</li> <li>• The possibility of programming group or individual work schedules, taking into account the permissible time of lateness and earlier exit</li> <li>• The distinction of standard events, overtime, lateness and earlier exits</li> <li>• Data export to USB flash memory in "*.xls" format</li> <li>• The device can signal when the shift ends with an audible signal</li> <li>• built-in battery - 2600 mAh</li> </ul>	...
Power supply	12 V DC / 1000 mA (power adapter included)	...
Weight	0.41 kg	...
Dimensions	181 x 136 x 32 mm	125 x 60 x 36 mm
Operation temp	0 °C ... 55 °C	...
Permissible relative humidity	10 % ... 90 %	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years