



	<a href="#">TV OR MONITOR MOUNT BRATECK-LCD-501N</a>	<a href="#">IP SPEED DOME CAMERA OUTDOOR DS-2DE7A220MCG-EB 6.7 ... 134 mm Hikvision</a>
		
	5.33 CAD 5.33 CAD	2404.63 CAD 2404.63 CAD
Standard	...	IP
Mounting standard	VESA 75, 100	...
Screen size range	max. 32 "	...
Bearing capacity	30 kg	...
Distance from mounting surface	88 mm from wall	...
Resolution	...	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Tilt adjustment	-15 ° ... 15 °	...
Sensor	...	1/1.8 " Progressive Scan CMOS
Horizontal rotation	-24 ° ... 24 °	...
Lens	...	6.7 ... 134 mm
Rotation in the plane of the screen	—	...
View angle	...	53 ° ... 4.9 °
Optical zoom	...	x 20
Digital zoom	...	x 16
Range of IR illumination	...	150 m
White light LED illuminator range	...	100 m
Video output	...	—
Preset rotation speed	...	• 240 °/s (horizontal) • 200 °/s (vertical)
Rotation speed (manual control)	...	• 0.1 °/s ... 160 °/s (horizontal) • 0.1 °/s ... 120 °/s (vertical)
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-15 ° ... 90 °
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	✓
Route settings	...	8
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	2 / 1

Audio	...	<ul style="list-style-type: none"> <li>• Audio input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Digital Noise Reduction,</li> <li>• Audio detection,</li> <li>• Speaker built-in - Alarm siren</li> <li>• Compliance with the AAC standard</li> </ul>
Main stream frame rate	...	25 fps @ 1080p
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	19.12
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Access from PC	...	Port no.: 8000 or access by a cloud (P2P) - PC : iVMS-4200 application
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
Mobile client access ports	...	8000
PC client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>
Intelligent image analysis	...	<ul style="list-style-type: none"> <li>• crossing the line (tripwire) - classification of people and vehicles</li> <li>• intrusion - classification of people and vehicles</li> <li>• detection of entry into the area / exit from the area - classification of people and vehicles</li> <li>• abandoned/missing object</li> <li>• face detection - detection of up to 5 faces simultaneously</li> <li>• advanced face capture features</li> </ul>



Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• EIS - Electronic Image Stabilization</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones - 24</li> <li>• Sharpness - sharper image outlines</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Auto White Balance</li> <li>• Intelligent 3D Positioning System</li> <li>• Intelligent Object Tracking</li> <li>• Active deterrence function - Light and sound alarm</li> <li>• Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> </ul>
Protections	...	<ul style="list-style-type: none"> <li>• Protection against lightning discharges : 6 kV</li> <li>• Overvoltage limiter, Overvoltage protection</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• Hi-PoE,</li> <li>• 24 V AC (power adapter included)</li> </ul>
Power consumption	...	≤ 42 W
Housing	...	Speed Dome, Metal
Color	Black	White
Operation temp	...	-30 °C ... 65 °C
"Index of Protection"	...	IP66
Mechanical protection class	...	IK10
Weight	0.524 kg	5.5 kg
Dimensions	115 x 115 x 88 mm	<ul style="list-style-type: none"> <li>• Ø 220 x 357 mm (without bracket)</li> <li>• Ø 220 x 387 x 453 mm (with bracket)</li> </ul>
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand	BRATECK	Hikvision
SAP Code	...	327000846
Guarantee	2 years	3 years