



	IP CAMERA APTI-AI802C3-28W-L Full-Color - 8.3 Mpx 4K UHD 2.8 mm	ACCESS POINT +ROUTER MAX18 Wi-Fi 6, 2.4 GHz, 5 GHz 574 Mbps + 1201 Mbps DAHUA
		
	318.40 PLN 318.40 PLN	288.00 PLN 288.00 PLN
Standard	TCP/IP	...
Frequency range	...	2.4 GHz, 5 GHz
Matrix size	8.3 Mpx	...
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS	...
Antenna type	...	<ul style="list-style-type: none"> • 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in
Standards	...	<ul style="list-style-type: none"> • LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2.8 mm	...
Baud rates	...	574 Mbps + 1201 Mbps
View angle	96 °	...
Protections	...	WPA2
White light LED illuminator range	25 m	...
LAN ports	...	3 x 10/100/1000 Mbps
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Main stream frame rate	25 fps @ 5 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Memory card slot	—	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • External microphone input - Cinch socket • Audio transmission via network • Compliance with the AAC standard 	...
WEB Server	Built-in	...

Max. number of on-line users	10	...
ONVIF	✓	...
RS-485 interface	—	...
Main features	...	<ul style="list-style-type: none"> • Support for Mesh technology, • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV • Easy and uniform management system for many devices - WiLynk application • Intuitive installation and configuration of many advanced functions
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Operation temp	...	-10 °C ... 55 °C
Default IP address	192.168.1.168	...
Permissible relative humidity	...	5 % ... 95 %
Default admin user / password	admin / admin The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	80	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...

Main features	<ul style="list-style-type: none"> • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • ICR - Movable InfraRed filter • Privacy zones • Image rotation and mirror • RESET button - on the cable • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of people gathering, loitering detection, motion detection based on human detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 370 mA 	12 V DC / 1.5 A (power adapter included)
Power consumption	≤ 4.4 W	≤ 12 W
Housing	Compact - Metal	...
Color	White	...
"Index of Protection"	IP67	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.45 kg	0.23 kg
Dimensions	172 x 73 x 73 mm	95 x 95 x 73 mm
Supported languages	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	DAHUA
Guarantee	2 years	2 years