



	FLUSH BOX 4-GANG M-4X60-F SIMET	FLUSH BOX 4-GANG PK-4X60/K-G/EPN Elektro- Plast	ACCESS POINT +ROUTER ARCHER-VR300 VDSL / ADSL 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP- LINK
			
	92.51 CZK 92.51 CZK	118.55 CZK 118.55 CZK	1572.59 CZK 1572.59 CZK
Number of sections	4	4	...
"Index of Protection"	IP20	—	...
Frequency range	2.4 GHz, 5 GHz
Antenna type	4 x Omnidirectional antenna 5 dBi
Material	Plastic	Plastic	...
Color	Orange	Brick red	...
Mounting holes distance	60 mm
Montage hole diameter	...	4 x Ø 67 mm	...
Standards	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
LAN ports	• 1 x 10/100 Mbps - LAN/WAN, • 3 x 10/100 Mbps - LAN
LED indicators	Power, DSL, INTERNET, WLAN, LAN
WAN interface	• 1 x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 • 1 x RJ-45
Transmitter power	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Baud rates	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	✓
Firmware update	✓
DDNS	• DynDNS • No-IP

Operation modes	ADSL/VDSL modem, Router, Access Point, Bridge WDS
Protections	<ul style="list-style-type: none"> • LAN : NAT, SPI network firewall, Access control, IP-MAC Binding, Support DoS defence, parental control • WLAN : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, QSS (Quick Secure Setup) - WPS
Management interface	Web browser, TP-LINK Tether
Main features	<ul style="list-style-type: none"> • Flush-mounted • 4 x 4 fixing points • 8 mounting screws, 6 cable partitions - included 	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • 4 special screws with holders to fastening to the wall - included 	<ul style="list-style-type: none"> • Enable/disable wireless network • SSID hiding • QoS • WMM (Wi-Fi Multimedia), • Rate limit • Internet access filtering • Wireless transmission statistics • Firewall • Remote management • DHCP : DHCP server, DHCP client list • Port forwarding : Virtual Server, Port Triggering, DMZ, ALG, UPnP • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, VPN Pass-through • IPv6 compliance • Static / dynamic routing • Port Mapping • IGMP Snooping V1/V2/V3 • Guest Network - a separate and secure network for guests • Built-in 4-port switch • ON/OFF button • WPS button • The WPS function allows to easy establish an encrypted connection • RESET button • The DSL line splitter included
Power supply	12 V DC / 1 A (power adapter included)
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 %
Weight	0.117 kg	0.088 kg	0.31 kg

Dimensions	284 x 71 x 63 mm	4 x Ø 60 x 47 mm - Internal dimensions 282 x 72 x 48 mm - External dimensions	257 x 160 x 37 mm
Manufacturer / Brand	SIMET	Elektro-Plast	TP-LINK
Guarantee	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00