






	EXTENDER ETHERNET+PoE ETH-ETH500-SET ATTE	EXTENDER EXT-POE4H IN A HERMETIC CASING PULSAR	SWITCHING ADAPTER DRS-24V30W-1AZ	HANDS-FREE SWITCH AD-TL-6497/DIMM 5 V - 24 V DC ORNO	REFLECTIVE LED LIGHTING CONTROLLER REFLECTIVE-SWITCH/BLEBOX 12 ... 24 V DC
					
	249.00 PLN 249.00 PLN	174.00 PLN 174.00 PLN	93.00 PLN 93.00 PLN	19.18 PLN 19.18 PLN	35.76 PLN 35.76 PLN
Adapter type	Switching
Input voltage	...	42 ... 57 V DC
Application	Works with LED lighting	Works with LED lighting - 12-24V LED strips
Power voltage	85 ... 264 V AC
LAN ports	2 x RJ45 10/100 Base-T + Passive PoE
Output voltage	...	42 ... 57 V DC	24 V DC
Rated voltage	5 V - 24 V DC	12 ... 24 V DC
LED diodes	LAN, PoE, 10Mb
Output voltage adjustment	21.6 ... 26.4 V
UTP transmission range	< 800 m (max)
Connector	...	3 x RJ-45 socket
Voltage tolerance	< 1 %
Maximal load	1.25 A
LED indicators	...	Link/Act
Output power	30 W
Transmission speed	10 / 100 Mbps : 2 LAN & PoE ports
Maximal total load	• 5 V = 40 W • 12 V = 96 W • 24 V = 120 W	60 ... 120 W
Total maximal current	8 A	5 A
Efficiency	88 %
Housing type	DIN
MTBF (Mean Time Between Faults)	700000 hours
Detection range	10 mm ... 60 mm	...
Detection method	Passive Infra Red (PIR)	...
Number of inputs	...	1	...	0	0
Number of outputs	...	2	1 pcs	1	1
Vibration resistance	IEC60068-2-6, 10 ... 150 Hz max. 2 G for 60 minutes
Supported data rates	...	• Range : 100 m - Input, 100 m - 2 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet
Maximal output power	< 250 m - 100 Mbps - 50 W < 500 m - 100 Mbps - 25 W < 800 m - 10 Mbps - 15 W
Connector type	PCB (soldering)	PCB (soldering)
Maximal total power	50 W
Wireless	—	—
Mobile phones support	—	—
Output power	...	max. 14.4 W / port PoE , max. 20 W (total)
Protections	...	• Overvoltage • Overload • Short-circuit	• Short-circuit • Overvoltage • Overload protection • Temperature

Main features	<ul style="list-style-type: none"> • Can be powered from a switch (PoE 802.3at/af, Passive PoE) and via screw connectors • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender • The output PoE voltage is equal to the input voltage 	<ul style="list-style-type: none"> • High power - max. 120 W • Possibility to adjust the light intensity depending on your needs • Small dimensions • Possible assembly in a profile • Simple and quick device installation 	<ul style="list-style-type: none"> • High power - max. 120 W, • Operation modes : NO, NC, bistable, • Turning off the light with the door not completely closed • Small dimensions, • Possible assembly in a profile
Housing	...	Plastic, hermetic	...	—	—
Operation temp. / Relative humidity	...	-10 ... 40 °C / 10 ... 90 %	-20 °C ... 70 °C / 5 % ... 95 %
"Index of Protection"	...	IP56	...	IP20	—
Power supply	44 ... 58 V DC - Passive PoE 12 ... 58 V DC - screw connectors
Color	—	—
Power consumption	1.35 W
Operation temp	-20 °C ... 50 °C
Weight	0.05 kg	0.55 kg	0.1 kg	0.001 kg	0.001 kg
Dimensions	73 x 52 x 20 mm (single element)	198 x 148 x 80 mm	21 x 89.5 x 75 mm	48 x 10 x 6 mm	38 x 10 x 4 mm
Manufacturer / Brand	ATTE	PULSAR	...	ORNO	BleBox
Guarantee	3 years	2 years	5 years	2 years	2 years