



	IP CAMERA DH-IPC-HFW4231SP-036 0B - 1080p 3.6 mm DAHUA	RJ45 CONNECTOR TOOL KIT NS-468/KIT
		
	630.00 PLN 630.00 PLN	38.48 PLN 38.48 PLN
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Scanning system	Progressive	...
Tested cables	...	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C), RJ12 (6P6C)
Resolution	1920 x 1080 - 1080p 1280 x 1024 - 1.4 Mpx 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Application	...	Plug RJ45 (8P8C) , Plug RJ12 (6P6C) , Plug RJ11 (6P4C) / DEC
Lens	3.6 mm	...
View angle	87 °	...
Range of IR illumination	30 m	...
S/N ratio	> 50 dB	...
RS-485 interface	—	...
Memory card slot	—	...
Image compression method	H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	—	...
Bitrate	24 ... 9472 kbps - H.264 14 ... 5632 kbps - H.265	...
Main stream frame rate	50 fps @ 1920 x 1080	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	2.42	...

Main features	<ul style="list-style-type: none"> • 3D-DNR - Digital Noise Reduction • WDR - 120 dB - Wide Dynamic Range • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • IVS analysis : crossing the line (tripwire), intrusion, scene changing, abandoned/missing object, face detection • Configurable Privacy Zones • Mirror - Mirror image 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	Battery 9 V 6LR61 (not included)
Power consumption	≤ 6 W	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS, Android: Free application IMOU • iOS (iPhone): Free application DMSS, iOS (iPhone): Free application IMOU 	...
Default admin user / password	admin / admin	...
Default IP address	192.168.1.108	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Housing	Compact - Metal	...
Color	White	...
Operation temp	-30 °C ... 60 °C	...
"Index of Protection"	IP67	...
Weight	0.400 kg	0.12 kg 0.77 kg (total)
Dimensions	162 x 70 x 70 mm	101 x 107 x 28 mm 260 x 170 55 mm (case)
Supported languages	English, Polish	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00