




	ROUTER RG-EG105G-V2 REYEE	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER RBD53G-5ACD2HND-LTE6 Chateau LTE6, Wi-Fi 5, 2.4 GHz, 5 GHz, 300 Mbps + 867 Mbps MIKROTIK	IP CAMERA IPC2125LE-ADF28KM-G - 5 Mpx 2.8 mm UNIVIEW
			
	584.25 PLN 584.25 PLN	668.66 PLN 668.66 PLN	750.00 PLN 750.00 PLN
Standard	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS
Matrix size	5 Mpx
WAN interface	• 1 x WAN x 10/100/1000 Mbps (RJ-45)
DDNS	✓
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	2.8 mm
Frequency range	...	• Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz	...
Port USB	—
Power supply PoE	—
View angle	• 113 ° (manufacturer data) • 104 ° (our tests result)
Range of IR illumination	50 m
S/N ratio	> 52 dB
RS-485 interface	—
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	—
Antenna type	...	• WiFi : 2 x 2 MIMO, Dual-chain - built-in 2 dBi @ 2.4 GHz 4 dBi @ 5 GHz, • LTE : 2 x 2 MIMO - built-in, SMA type connectors	...

Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection
Main stream frame rate	25 fps @ 5 Mpx
Network interface	10/100 Base-T (RJ-45)
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, 4G+ Cat.6 LTE, 3G - DC-HSPA+/HSPA/UMTS	...
Baud rates	...	<ul style="list-style-type: none"> • Wi-Fi : 300 Mbps + 867 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps 	...
LAN ports	<ul style="list-style-type: none"> • 3 x LAN 10/100/1000 Mbps (RJ-45) • 1 x LAN/WAN 10/100/1000 Mbps (RJ-45) 	5 x 10/100/1000 Mbps - LAN	...
Permissible relative humidity	10 % ... 90 % (non-condensing)
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP
WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Mobile phones support	Android: Free application Ruijie Rejee iOS (iPhone): Free application Ruijie Rejee	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80



Receiver sensitivity	...	<ul style="list-style-type: none"> 5 GHz : • 6M : -96 dBm • 54M : -80 dBm • MCS0 : -96 dBm • MCS7 : -75 dBm • MCS9 : -70 dBm 2.4 GHz : • 1M : -100 dBm • 6M : -96 dBm • 11M : -94 dBm • 54M : -78 dBm • MCS0 : -96 dBm • MCS7 : -73 dBm 	...
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Transmitter power	...	<ul style="list-style-type: none"> • 5 GHz : < 26 dBm • 2.4 GHz : < 26 dBm 	...
LED indicators	Status, Link/Act	Power, WLAN, LAN, Signal indicator	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire)
Housing	Compact, Metal + Plastic
Color	White
"Index of Protection"	IP67
Vandal-proof	—



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network type	...	<ul style="list-style-type: none"> • 4G : FDD-LTE B1/B3/B5/B7/B8/B20/B28 - 2100 / 1800 / 850 / 2600 / 900 / 800 / 700 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 ... / 2500 MHz • 3G : DC- HSPA+/HSPA/UMTS B1/B3/B5/B8 - 2100 / 1800 / 850 / 900 MHz 	...
LTE	...	✓	...
Operation temp	-30 °C ... 60 °C
DHCP server	✓	✓	...
Firmware update	✓	✓	...
Protections	<ul style="list-style-type: none"> • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping 	Firewall	...
Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Rejee application • Remote management • Web browser 	Web browser	...
Default IP address	...	192.168.88.1	DHCP or 192.168.1.13
Operating system	...	MikroTik RouterOS	...
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian



Main features	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • View topology and network status • RESET button 	<ul style="list-style-type: none"> • Built-in 3G/4G/LTE modem, no SIMLOCK - The microSIM cards support • SMA connector for connecting an external antenna (LTE) - 2 pcs • Port USB 2.0 - USB-A socket, 1 A (max) • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Dual-chain • VPN support • VLAN support • parental control • IPsec • SMS personal messaging • e-mail personal messaging • WPS button • The WPS function allows to easy establish an encrypted connection • Mode button • RESET button • Ethernet network cable, UTP cat. 5e (included) 	...
Power supply	12 V DC / 0.5 A (power adapter included)	12 ... 28 V DC - 24 V DC / 1.2 A (power adapter included)	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA
Power consumption	max. 6 W	max. 21 W	≤ 6 W
Operation temp	0 °C ... 40 °C	-40 °C ... 70 °C	...
Weight	0.4 kg	0.642 kg	0.45 kg
Dimensions	207 x 109 x 28 mm	240 x 156 x 51 mm	190 73 x 71 mm
Manufacturer / Brand	RUIJIE / REYEE	MikroTik	UNIVIEW
Guarantee	2 years	2 years	3 years