



	SWITCH POE GTX-C1-10-8G2G 8-PORT	BLANK MODULE AD-LS/ZP-45X45 System 45
		
	366.40 PLN 366.40 PLN	3.15 PLN 3.15 PLN
Application	...	System 45
Material	...	Plastic
Color	...	White
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	...
Manufacturer / Brand	...	STASINSKI / JAVEL
Management	—	...
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act, Speed	...
Transmission speed	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE	...
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports 	...
Maximal total power	120 W	...
MAC addresses table	2k	...

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	...
Certificates	CE, FCC Class B	...
Protections	Overvoltage \pm 4 kV	...
Power supply	100 ... 265 V AC	...
Operation temp	-10 °C ... 45 °C	...
Weight	0.79 kg	0.006 kg
Dimensions	210 x 150 x 35 mm	45 x 45 x 16 mm
Guarantee	2 years	2 years