



	IP SPEED DOME CAMERA OUTDOOR IPC6312LR-AX4W-VG Wi-Fi, - 1080p 2.8 ... 12 mm UNIVIEW	POWER SUPPLY ADAPTER 12-24V/4A/TAY
		
	1541.19 PLN 1541.19 PLN	45.61 PLN 45.61 PLN
Standard	TCP/IP	...
Adapter type	...	Switching
Power voltage	...	100 ... 240 V AC
Sensor	1/2.7 " Progressive Scan CMOS	...
Frequency range	...	50/60 Hz
Matrix size	2.1 Mpx	...
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	2.8 ... 12 mm	...
Output voltage	...	12 V, 15 V, 16 V, 18 V, 19 V, 20 V, 24 V DC
Maximal load	...	4.5 A @ 12, 15, 16, 18, 19 V 4 A @ 20, 24 V
View angle	• 105 ° ... 29 ° (manufacturer data) • 83 ° ... 30 ° (our tests result)	...
Optical zoom	x 4	...
Digital zoom	—	...
Range of IR illumination	50 m	...
Video output	—	...
Application	...	Recorders, cameras, notebooks, monitors, printers, scanners
Preset rotation speed	• 50 °/s (horizontal) • 40 °/s (vertical)	...
Output	...	10 pcs 6.50/4.40mm, 2 x 5.50/2.50mm, 3.50/1.35mm, 6.30/3.00mm, 2 x 4.80/1.70mm, 5.50/3.00mm, 7.40/5.00mm, 8.0/5.50mm
Rotation speed (manual control)	• 0.1 °/s ... 50 °/s (horizontal), • 0.1 °/s ... 40 °/s (vertical)	...
Horizontal rotation range	0 ° ... 345 ° - Rotation of the head is limited by stops	...
Vertical rotation range	-10 ° ... 110 °	...
RS-485 interface	—	...
Number of presets	256	...
Horizontal scan	—	...
Route settings	16	...

Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Bi-directional audio streaming support • Audio detection • Noise reduction 	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	<ul style="list-style-type: none"> • Wi-Fi, 2.4 GHz, IEEE 802.11 b/g/n, • 10/100 Base-TX (RJ-45) 	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...



Main features	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Support ARP defence • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • RESET button - on the cable • Privacy zones - max. 4 • Motion Detection • Tamper signaling • Image rotation and mirror • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • Home Position - set the camera to the specified position if no operator activity for a specified dwell time • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, abandoned/missing object, scene changing, people counting, crowd gathering estimation, face detection 	...
Housing	Speed Dome, Plastic	...
Color	White + Black	...
"Index of Protection"	IP66	...
Vandal-proof	—	...
Power supply	12 V DC / 1 A	...
Power consumption	≤ 12 W	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.85 kg	0.27 kg
Dimensions	Ø 133 x 185 x 276 mm (without bracket)	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00