





	<a href="#">EXTENDER WITH SPLITTER HDMI-SP-EX-6IR</a>	<a href="#">ACCESS CONTROLLER MODULE MC16-PAC-EX-1 ROGER</a>	<a href="#">TOOL FOR CLEANING FIBER OPTIC CONNECTORS WUN-014 FC / SC / ST</a>	<a href="#">SFP DUMMY PLUG PPZO- SFP/B</a>
				
	270.40 PLN 270.40 PLN	1400.00 PLN 1400.00 PLN	124.94 PLN 124.94 PLN	1.71 PLN 1.71 PLN
Application	...	...	...	SFP dummy plug
Number of served transitions	...	1	...	...
Material	...	...	...	Rubber
Inputs	...	8	...	...
Color	...	...	...	Black
Outputs	...	8	...	...
Number of users	...	max. 12000 - Number of identifiers	...	...
Application	...	...	Ideal for removing dirt from optical components Connector type : FC / SC / ST	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...	...
Supported HDMI resolutions	1080p, 1080i, 720p, 576p, 576i, 480p, 480i	...	...	...
Number of permissions per ID	...	100	...	...
Buffer memory	...	8 000 000 events buffer	...	...
MCT readers support	...	16 pcs	...	...
Readers connections	...	4 pcs - Wiegand / PRT	...	...
Number of login points	...	2	...	...
Number of access terminals	...	4	...	...
Number of access zones	...	2	...	...
Number of alarm zones	...	2	...	...
Maximal transmission range	• 60 m @ 1080p - UTP cat. 6 (manufacturer data) • 45 m @ 1080p - UTP cat. 5e (our tests result) • 15 m @ HDMI cable	...	...	...
Number of automation nodes	...	2	...	...
Battery backup support	...	12 V / 7 Ah	...	...
Supported audio formats	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD	...	...	...
Communication	...	• Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)	...	...

Main features	IR receiver : 20 ... 60 kHz	<ul style="list-style-type: none"> <li>• Integrated support in VISO EX software</li> <li>• Functions in the VISO EX system: - MSSQL database</li> <li>- work in distributed systems</li> <li>- multi-station work</li> <li>- monitoring of transitions with video preview</li> <li>- T&amp;A event reporting</li> <li>- maximum number of transitions in the system - unlimited</li> <li>- division of the system into partitions operated by independent operators</li> <li>- tool for integration with RACS5 (API) systems</li> <li>- integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)</li> </ul>	...	...
Power supply	5 V DC / 1000 mA - 2 pcs of power adapters included	<ul style="list-style-type: none"> <li>• 17 ... 22 V AC</li> <li>• 10 ... 15 V DC</li> <li>• 22 ... 26 V DC</li> </ul>	...	...
Operation temp	...	5 °C ... 40 °C	...	...
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	...	...
Weight	0.085 kg	0.14 kg	0.02 kg	0.0005 kg
Dimensions	67 x 71 x 25 mm	175 x 72 x 30 mm	178 x 17 x 17 mm	15 x 14 x 9 mm
Manufacturer / Brand	...	ROGER	...	...
Guarantee	2 years	3 years	...	2 years