

	ALLEN SCREW SL-M8X25/KL-8.8	FRONT MOUNTING BASE USP-UDMK-P FOR SOLAR PANELS	NVR NVR4232-4KS3 32 CHANNELS DAHUA
			
	0.19 CHF 0.19 CHF	6.60 CHF 6.60 CHF	430.50 CHF 430.50 CHF
Size	M8
Standard	TCP/IP
Material	Steel galvanized	Aluminum	...
Strength class	8.8
Supported resolutions	max. 12 Mpx - 4000 x 3000 px
Main features	DIN 912 compliance
Video outputs	1 pcs HDMI 4K 1 pcs VGA
Wrench size	6 mm
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support
Thread length	25 mm
Audio inputs	1 pcs CINCH
Audio outputs	1 pcs CINCH
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264
Bitrate	max. 160 Mbps
Supported hard drives	2 x 20 TB SATA
Recording modes	Manual, Sensor, Motion detection, Schedule
External storage devices backup	Backup to USB drive (pendrive, external drive)
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 16 channels in the same time
Network interface	1 x RJ-45 10/100/1000 Base-TX
Network functions	Full support via network, Remote records copying, Web-Server built-in
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UDP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, FTP, DDNS, SNMP, Alarm Server, P2P, Auto Register, IP Search
ONVIF	2.2.12
Default IP address	192.168.1.108
Default admin user / password	admin / admin The administrator password should be set at the first start
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
RTSP URL	<ul style="list-style-type: none"> • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

USB	2 pcs USB 2.0
Serial ports	—
Alarm inputs / outputs	4 / 2
PTZ control	IP Speed Dome Cameras
Motion Detection	✓
Intelligent image analysis	✓
Main features	<ul style="list-style-type: none"> • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Privacy zones <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • Intelligent image analysis : perimeter protection, scene changing • face detection - supports 6 types of facial attributes extraction • Face recognition • people counting • heat map
Mouse support	✓
IR remote controller in the set	—
Power supply	12 V DC / 4 A (power adapter included)
Power consumption	max. 10 W (without HDD)
Operation temp	-10 °C ... 55 °C
Weight	0.014 kg	0.17 kg	1.5 kg
Dimensions	Ø 12.8 x 33.0 mm	96 x 80 x 73 mm	375 x 283 x 53 mm
Supported languages	Polish, English
Manufacturer / Brand	DAHUA
Guarantee	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00