



	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE56D0T-IT3F(3.6mm) - 1080p Hikvision	IP CAMERA IPC2124LB-ADF28KM-H - 3.7 Mpx 2.8 mm UNIVIEW
		
	20480.77 HUF 20480.77 HUF	61779.81 HUF 61779.81 HUF
Standard	AHD / HD-CVI / HD-TVI / PAL	TCP/IP
Sensor	Progressive Scan CMOS	1/2.9 " Progressive Scan CMOS
Matrix size	2.1 Mpx	4 Mpx
IR illuminator power adjustment	Automatic	...
Resolution	1920 x 1080 - 1080p	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	3.6 mm	2.8 mm
IR illuminator support	ICR - Movable InfraRed filter	...
View angle	• 82 ° (manufacturer data) • 78 ° (our tests result)	102 °
Range of IR illumination	40 m	30 m
S/N ratio	> 62 dB	> 52 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	...
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
OSD menu	—	...
Audio	...	• Microphone built-in, • Audio transmission via network, • Audio detection
Main stream frame rate	...	20 fps @ 4 Mpx 25 fps @ 3 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
SAP Code	300609182	...

Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • DNR - Digital Noise Reduction • Auto White Balance 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines
Power supply	12 V DC / 330 mA	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA
Power consumption	≤ 4 W	≤ 5.5 W
Housing	Dome, Plastic	Compact, Metal + Plastic
Color	White	White
"Index of Protection"	IP66	IP67
Vandal-proof	—	—
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.24 kg	0.38 kg

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Dimensions	Ø 110 x 93 mm	166 x 63 x 62 mm
Supported languages	...	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	Hikvision	UNIVIEW
Guarantee	3 years	3 years