




	POLE MOUNT USH-M4	POLE MOUNT PFA152-E DAHUA	ACCESS POINT 5.8 GHz CDS-6IP/ECO CAMSAT
			
	72.31 PLN 72.31 PLN	105.00 PLN 105.00 PLN	639.00 PLN 639.00 PLN
Suitable for cameras	...	DAHUA - documentation for download below.	...
Support	SH-567/426/369
Number of fastening elements	2
Pole diameters range	...	Ø 80 ... Ø 150 mm	...
Mast diameter	Ø 50 mm (max)
Material	Magnelis - carbon steel, coated with a zinc-aluminum-magnesium alloy	Aluminum	...
Frequency range	5180 MHz ... 5350 MHz , 5470 MHz ... 5725 MHz
Plate thickness	2 mm
Color	...	White	...
Mounting holes distance	<ul style="list-style-type: none"> • 165 mm, • 510 mm
Protections	<ul style="list-style-type: none"> • 64 / 128 / 152 bits WEP code • WPA • WPA-PSK/WPA2-PSK
Transmitter power	≤ 500 mW (27 dBm)
Wireless transmission range	max. 2 km
Antenna type	Integrated, 2 pcs 14 dBi MIMO - Interpolarized H/V
Modulation type	OFDM
Baud rates	max. 60 Mbps
Operation modes	<ul style="list-style-type: none"> • Video Bridge - mode dedicated to work with IP cameras • Master - Access Point • Slave - AP Client
Power supply	<ul style="list-style-type: none"> • Passive PoE : 48 V DC (using an external adapter) • 12 V DC / 1 A (power adapter included)
Power consumption	≤ 11 W

Main features	Mounting to the mast with u-bolts	...	<ul style="list-style-type: none"> • Operates in configuration Point-to-Point and Point-to-Multipoint • MIMO technology - increases the throughput of wireless link (multiple antennas transmission) • Bidirectional communication • IP PTZ control • RF power control • interference free transmission (industrial, 802.11, Bluetooth, radiotelephony, etc.)
"Index of Protection"	IP55
Operation temp	-20 °C ... 70 °C
Weight	2.04 kg	0.260 kg	0.35 kg
Dimensions	...	126 x 114 x 20 mm	249 x 88 x 52 mm
Manufacturer / Brand	...	DAHUA	CAMSAT
Guarantee	2 years	3 years	2 years