







	CABLE TIE HOLDER PS-5-20X20/B*P50	SINGLE- AND MULTI-MODE MEDIA CONVERTER TXRX SET OM2-20WDM	EXTENDER EXT-POE3H IN A HERMETIC CASING PULSAR	VIDEO AMPLIFIER VCA-1/2000	AHD, HD-CVI, HD-TVI CAMERA APTI- H50PV21-28W 2Mpx / 5Mpx 2.8 mm	GSM ADAPTER CABLE SMA-G/TS9-0.2M-V2
						
	3.32 EUR 3.32 EUR	79.81 EUR 79.81 EUR	67.68 EUR 67.68 EUR	27.47 EUR 27.47 EUR	23.29 EUR 23.29 EUR	3.57 EUR 3.57 EUR
Optical connector type	...	SC
Number of fibers	...	1 pcs
Cable	SMA socket / TS9
Standard	CVBS - PAL / NTSC
Standard	AHD, HD-CVI, HD-TVI	...
Length of the cable	0.2 m
Device type	Active
In package	50 pcs The price for package
Sensor	1/3 " Progressive Scan CMOS	...
Transmission range	...	• 2 km Multi-mode fiber, • 20 km Single-mode fiber
Standards	PoE : 802.3af/at - Port PoE OUT 1/2, Passive PoE - Port PoE OUT 3
Holes dimensions	5 x 2 mm
Matrix size	5 Mpx	...
Input voltage	42 ... 57 V DC
Number of channels	1 Video
Montage hole diameter	Ø 4 mm
Supported standards	...	IEEE 802.3, IEEE 802.3u
Output voltage	42 ... 57 V DC
Video transmission range	max. 2000 m
Port LAN	...	1 pcs (RJ-45. UTP/STP)
Number of inputs	1
Application	HUAWEI E938 NOVATEL SIERRA ZTE AnyData
Transmission speed	...	10/100 Mbps
Number of outputs	3
Video bandwidth	0 ... 9 MHz
Assembly	• The bottom layer is equipped with a Scotch tape, • Mounting with screws
MTU	...	max. 1600 B
Connector	4 x RJ-45 socket
Coaxial socket impedance	75 Ω
Optical wavelength	...	1550 / 1310 nm
LED indicators	LAN, PoE
Coaxial socket type	2 x BNC Straight socket
Main features	...	• MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Auto detection of the bit rate • Bi-directional transmission via single fiber • LED indicators showing operating status • Wavelength-Division Multiplexing technology WDM (Tx 1550nm / Rx 1310nm)	...	• Distance range switch built-in • Signal correction	...	Very easy and quick assembly
Operation temp	...	0 °C ... 60 °C
Supported data rates	• Range : 100 m - Input, 100 m - 3 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet.



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Resolution	• 2592 x 1944 - 5 Mpx @ AHD, HD-TVI, • 2560 x 1440 - 3.7 Mpx @ AHD, HD-TVI, HD-CVI, • 1920 x 1080 - 1080p @ AHD, HD-CVI, HD-TVI	...
Range of IR illumination	20 m	...
Permissible relative humidity	...	5 % ... 90 %
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
Output power	19.2 W / Port PoE OUT 1/2 , 14.4 W / Port PoE OUT 3 , max. 19.2 W (total)
View angle	• 89 ° (manufacturer data) • 83 ° (our tests result)	...
Protections	• Overvoltage • Overload • Short-circuit
Video output	1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI - selectable by switch	...
Operation temp. / Relative humidity	-25 ... 50 °C / 10 ... 90 %
Main features	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Sharpness - sharper image outlines • Auto White Balance	...
Power supply	...	5 VDC / 1.2 A (power adapter included), (2.5/5.5mm socket)	...	12 V / 60 mA (power adapter not included)	12 V DC / 180 mA	...
Power consumption	≤ 2.2 W	...
OSD menu	OSD menu available via recorder	...
Housing	Plastic, hermetic	...	Dome - Plastic	...
Color	Black	White	...
"Index of Protection"	IP56	...	—	...
Vandal-proof	—	...
Operation temp	-20 °C ... 60 °C	...
Weight	...	0.180 kg	0.55 kg	0.07 kg	0.11 kg	...
Dimensions	20 x 20 x 8 mm	104 x 70 x 26 mm	198 x 148 x 80 mm	120 x 61 x 30 mm	Ø 84 x 69 mm	...
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	...
Manufacturer / Brand	PULSAR	DELTA	APTI	...
Guarantee	2 years	2 years	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00