

	CONNECTOR STRIP WAGO-2273-202*P100	CAMERA AHD-LC4-2812 - 720p 2.8 ... 12 mm
		
	15.49 GBP 15.49 GBP	39.42 GBP 39.42 GBP
Standard	...	AHD
Sensor	...	1/4 " OmniVision OV9712S CMOS
Digital Image Processor	...	Nextchip NVP2431H
Matrix size	...	1.0 Mpx
In package	100 pcs The price for package	...
Number of terminal pairs	1	...
Connector type	2 x spring terminal	...
Resolution	...	1280 x 720 - 720p AHD-M
Wire gauge	0.5 ... 2.5 mm ² - Wire	...
Nominal voltage	450 V	...
Rated current	24 A	...
Range of IR illumination	...	40 m
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 ... 12 mm, 2 Mpx
View angle	...	<ul style="list-style-type: none"> • 65 ° ... 17 ° (manufacturer data) • 65 ° ... 25 ° (our tests result)
S/N ratio	...	> 50 dB
Video output	...	1 Vpp 75 Ω, AHD - selectable by switch

Main features	...	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • Sense-UP - (Slow Shutter) - Increase the sensor sensitivity max. x 30 • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • Motion Detection - max. 4 zones • Privacy zones - max. 4 • BLC - configurable Back Light Compensation • HSBLC - High Light Compensation (spot) • Mirror - Mirror image • image "freeze" • Sharpness - sharper image outlines • Monitor type correction - LCD/CRT
OSD menu	...	✓
"Index of Protection"	...	IP66
Power supply	...	12 V DC / 460 mA
Housing	...	Compact, Metal
Color	Black	Graphite
Operation temp	...	-20 °C ... 50 °C
Weight	...	0.69 kg
Dimensions	16 x 9 x 4 mm	288 x 91 x 85 mm
Supported languages	...	English, Chinese, French, Spanish, Dutch, German, Polish, Portuguese, Russian, Turkish, Italian
Guarantee	2 years	2 years