

	BATTERY ENCLOSURE R-AKU2 TO RACK CABINET PULSAR	IP CAMERA APTI-RF42MAP-37 Wi-Fi, PINHOLE - 4 Mpx 3.7 mm	UNIVERSAL CLEANING WIPES IPA-WIPE/25 AG TERMOPASTY
			
	159.00 PLN 159.00 PLN	318.40 PLN 318.40 PLN	40.58 PLN 40.58 PLN
Width	19 "
Standard	...	TCP/IP	...
Sensor	...	1/3 " Progressive Scan CMOS	...
In package	25 wipes - The price for package
Height	2 U
Matrix size	...	4 Mpx	...
Material	Steel - powder painted
Application	<ul style="list-style-type: none"> • Cleaning the optics • Removal of dirt from precision mechanical components
Wipe dimensions	160 x 125 mm
Application	Batteries : <ul style="list-style-type: none"> • 2 x 17 Ah / 12 V, • 4 x 7 Ah / 12 V
Resolution	...	2688 x 1512 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Main features	<ul style="list-style-type: none"> • Corrosion resistance • 4 pcs. of M6 screws with cage nuts included
Lens	...	3.7 mm (pinhole)	...
View angle	...	<ul style="list-style-type: none"> • 70 ° (manufacturer data) • 90 ° (our tests result) 	...
S/N ratio	...	> 52 dB	...
Min. illumination	...	0.01 Lux @ F1.6 (AGC off)	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	...	1 / -	...
Main stream frame rate	...	25 fps - 4 Mpx	...
Network interface	...	<ul style="list-style-type: none"> • 10/100 Base-T (RJ-45) • Wi-Fi - IEEE 802.11 b/g/n 	...
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP	...

Audio	...	<ul style="list-style-type: none"> • Audio input - Jack 3.5 mm socket • Audio output - Jack 3.5 mm socket • Bi-directional audio streaming support 	...
ONVIF	...	2.4	...
RS-485 interface	...	—	...
Memory card slot	...	Micro SD memory cards up to 512GB support (possible local recording)	...
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Default IP address	...	192.168.1.168	...
Default admin user / password	...	admin / admin	...
Web browser access ports	...	80	...
PC client access ports	...	80	...
WEB Server	...	Built-in Built-in	...
Mobile client access ports	...	80	...
Max. number of on-line users	...	10 10	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...



Main features	...	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • F-DNR (Defog) - Reduction of image noise caused by precipitation • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable: brightness, contrast, saturation • Mirror - Mirror image • Sharpness - sharper image outlines • Intelligent image analysis : intrusion 	...
Power supply	...	12 V DC / 190 mA	...
Power consumption	...	≤ 2.3 W	...
Housing	...	Mini - Metal	...
Color	Black - RAL9004	Black	...
Operation temp	...	-20 °C ... 60 °C	...
Weight	1.7 kg	0.14 kg	...
Dimensions	425 x 175 x 85 mm Internal dimensions 483 x 180 x 90 mm External dimensions	37.5 x 37.5 x 30 mm	...
Supported languages	...	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	PULSAR	APTI	AG TERMOPASTY
Guarantee	2 years	2 years	2 years

