



	<a href="#">IP SPEED DOME CAMERA OUTDOOR SD5A445GB-HNR - 3.7 Mpx 3.96 ... 177.75 mm DAHUA</a>	<a href="#">RJ-45 PLUG INTERNAL SHIELD RJ45/WP-T/INF*P100</a>
		
	9151.00 PLN 9151.00 PLN	20.00 PLN 20.00 PLN
Standard	TCP/IP	...
Sensor	1/2.8 " STARVIS™ CMOS	...
Matrix size	4 Mpx	...
In package	...	<b>100 pcs The price for package</b>
Application	...	RJ-45 modular plug internal shield
Material	...	Rubber
Resolution	2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 720p	...
Lens	3.96 ... 177.75 mm	...
View angle	• 66 ° ... 1.9 ° (manufacturer data) • 59 ° ... 1.9 ° (our tests result)	...
Optical zoom	x 45	...
Digital zoom	x 16	...
Range of IR illumination	150 m	...
Video output	—	...
Preset rotation speed	• 400 °/s (horizontal) • 300 °/s (vertical)	...
Rotation speed (manual control)	• 0.1 °/s ... 300 °/s (horizontal) • 0.1 °/s ... 200 °/s (vertical)	...
Horizontal rotation range	360 ° - continuous	...
Vertical rotation range	-15 ° ... 90 °	...
RS-485 interface	—	...
Number of presets	300	...
Horizontal scan	✓	...
Route settings	8	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	2 / 1	...
Audio	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...

Network protocols	HTTP, HTTPS, TCP/IP, PPPoE, IPv4/IPv6, RTMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IEEE 802.1x, QoS, FTP, UPnP, ICMP, SNMP, SSL, IGMP, ARP, RTCP, RTP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	21.12	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">DMSS</a> • iOS (iPhone): Free application <a href="#">DMSS</a>	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> <li>• Intelligent Object Tracking</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• EIS - Electronic Image Stabilization</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms</li> <li>• Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Motion Detection</li> <li>• Privacy zones - max. 24</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> <li>• IVS analysis : crossing the line (tripwire), intrusion, abandoned/missing object, fast moving, parking detection, detection of people gathering, loitering detection, face detection - advanced face capture features, supports 6 types of facial attributes extraction</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles (tripwire, intrusion)</li> </ul>	...

Power supply	• PoE (802.3at), • 24 V DC / 2.5 A (power adapter included)	...
Power consumption	max. 22 W	...
Housing	Speed Dome, Metal + Plastic	...
Color	White + Black	(transparent)
Operation temp	-40 °C ... 70 °C	...
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Weight	5.34 kg (with bracket)	0.001 kg
Dimensions	190 x 415 x 268 mm (with bracket)	27 x 12 x 15 mm
Supported languages	Polish, English, Czech, Spanish, French, Dutch, German, Portuguese Romanian, Russian Turkish Hungarian, Italian	...
Manufacturer / Brand	DAHUA	...
Guarantee	5 years	2 years

