



	HANDLE WITH REPLACEABLE BITS WH- SFE/PACK-1/17/SLIMVARIO WIHA	IP CAMERA APTI-AI401CA3-36W - 4 Mpx 3.6 mm
		
	438.42 PLN 438.42 PLN	232.00 PLN 232.00 PLN
Standard	...	TCP/IP
Matrix size	...	4 Mpx
Number of replaceable bits	14 pcs	...
Sensor	...	1/3 " Progressive Scan CMOS
Resolution	...	2688 x 1512 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	3.6 mm
View angle	...	81 °
Range of IR illumination	...	25 m
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Memory card slot	...	—
Alarm inputs / outputs	...	—
Bits sizes	Philips : PH1, PH2 , Pozidriv : PZ1, PZ2 , Standard/Slotted : 2.5 mm, 3.0 mm, 4.0 mm, 5.5 mm , Flat-cross : SL/PZ1, SL/PZ2 , Torx : T10, T15, T20, T25	...
Arrowhead length	75 mm	...
Voltage insulation	1000 V	...
Audio	...	• External microphone input, • Compliance with the AAC standard
WEB Server	...	Built-in
Max. number of on-line users	...	10
ONVIF	...	✓
RS-485 interface	...	—
Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168

Default admin user / password	...	admin / admin The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@ip_address:80/0 - Main stream • rtsp://user:password@ip_address:80/1 - Sub stream
AC voltage range	110 V ... 250 V	...
Main features	<ul style="list-style-type: none"> • Insulation made in accordance with VDE • Compliance with IEC 60900 standard • GS quality mark • Handle compatible with slimBit system • Insulation made in accordance with VDE • Compliance with IEC 60900 standard • GS quality mark • Ergonomically shaped handle protects tendons and joints during operation • Insulation made in accordance with VDE • GS quality mark 	...



Main features	...	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection, video tampering • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Mirror - Mirror image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Day/Night mode - configurable • RESET button - on the cable • Privacy zones - max. 3 • Sharpness - sharper image outlines
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 290 mA
Power consumption	...	≤ 3.5 W
Housing	Plastic	Compact - Metal
Color	...	White
"Index of Protection"	...	IP67
Operation temp	...	-20 °C ... 60 °C
Weight	0.323 kg (total)	0.44 kg
Dimensions	Ø 29 x 160 mm Ø 18 x 140 mm	173 x 73 x 73 mm
Supported languages	...	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	WIHA	APTI
Guarantee	2 years	2 years