



	VIDEO SEPARATOR SV-1000P STANDARD: PAL	INDUSTRIAL POE SWITCH GTX-P1-5-41GSFP 4-PORT SFP
		
	141.29 PLN 141.29 PLN	376.00 PLN 376.00 PLN
Standard	CVBS - PAL / NTSC	...
Number of inputs	1 pcs BNC	...
Number of outputs	1 pcs BNC	...
Input impedance	75 Ω	...
Output impedance	75 Ω	...
Galvanic (optical) isolation between signal inputs and outputs	1000 V peak	...
Opto-isolation between power and signal inputs / outputs	1000 V peak	...
Gain adjustment	-5 dB ... +5 dB	...
Bandwidth	9 MHz / 1 Vpp	...
Transmission error	0.75 % (f=3.58MHz, Vin=1Vpp)	...
LAN ports	...	<ul style="list-style-type: none"> • 4 x RJ45 10/100 Base-T (2 x Hi-PoE + 2 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-T - Uplink, • 1 x Port SFP 1000 Base-X - Uplink
Assembly	To the wall	...
Management	...	—
Manufacturer / Brand	DELTA	...
LED diodes	...	Power, PoE, Link/Act
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps : 4 x Port LAN & PoE, • 10 / 100 / 1000 Mbps : 1 x Port RJ45 (Uplink), • 1000 Mbps : 1 x Port SFP (Uplink)
Operation modes	...	<ul style="list-style-type: none"> • 250 m (Extend) - Range : 250 m @ 10 Mbps • VLAN - 1 ... 4 ports are isolated from each other and separately work with the 5, 6 ports • PD Alive • Port PoE Priority

Maximal output power	...	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - 1, 2 ports • 30 W / port PoE 802.3af/at - 3, 4 ports
Main features	...	<ul style="list-style-type: none"> • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • Ports 1 ... 4 support transmission priorities • The ability to connect two power adapters - redundant power supply • Industrial wide temperature design. • "Index of Protection" : IP40 • Devices for mounting on a DIN, TS-35 rail
Certificates	...	CE, FCC, RoHS
Protections	...	<ul style="list-style-type: none"> • Overvoltage : 6 kV • Contact/Air (ESD/EMP) : 6/8 kV
Power supply	12 V DC / 80 mA	48 ... 57 V DC - 2.1/5.5 mm socket or screw terminals (power adapter not included)
Operation temp	...	-40 °C ... 75 °C
Weight	0.095 kg	0.5 kg
Dimensions	61 x 120 x 30 mm	145 x 103 x 45 mm
Guarantee	3 years	2 years