



	ACCESS CONTROLLER MODULE MC16-PAC-ST-2 ROGER	ACCESS POINT +ROUTER ARCHER-VR300 VDSL / ADSL 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP- LINK
		
	1390.00 PLN 1390.00 PLN	264.51 PLN 264.51 PLN
Number of served transitions	2 (two-way)	...
Number of supported readers	8	...
Frequency range	...	2.4 GHz, 5 GHz
Number of users	unlimited (purchase of the appropriate license required)	...
Antenna type	...	4 x Omnidirectional antenna 5 dBi
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Buffer memory	8 000 000 events buffer	...
Number of access zones	4	...
Number of alarm zones	4	...
Battery backup support	12 V / 7 Ah	...
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...
Standards	...	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
LAN ports	...	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN, • 3 x 10/100 Mbps - LAN
LED indicators	...	Power, DSL, INTERNET, WLAN, LAN

WAN interface	...	<ul style="list-style-type: none"> • 1 x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 • 1 x RJ-45
Transmitter power	...	<ul style="list-style-type: none"> < 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Baud rates	...	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	...	✓
Firmware update	...	✓
DDNS	...	<ul style="list-style-type: none"> • DynDNS • No-IP
Operation modes	...	ADSL/VDSL modem, Router, Access Point, Bridge WDS
Protections	...	<ul style="list-style-type: none"> • LAN : NAT, SPI network firewall, Access control, IP-MAC Binding, Support DoS defence, parental control • WLAN : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, QSS (Quick Secure Setup) - WPS
Management interface	...	Web browser, TP-LINK Tether

Main features	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Enable/disable wireless network • SSID hiding • QoS • WMM (Wi-Fi Multimedia), • Rate limit • Internet access filtering • Wireless transmission statistics • Firewall • Remote management • DHCP : DHCP server, DHCP client list • Port forwarding : Virtual Server, Port Triggering, DMZ, ALG, UPnP • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, VPN Pass-through • IPv6 compliance • Static / dynamic routing • Port Mapping • IGMP Snooping V1/V2/V3 • Guest Network - a separate and secure network for guests • Built-in 4-port switch • ON/OFF button • WPS button • The WPS function allows to easy establish an encrypted connection • RESET button • The DSL line splitter included
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC / 1 A (power adapter included)
Operation temp	5 °C ... 40 °C	0 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	10 % ... 90 %
Weight	0.14 kg	0.31 kg
Dimensions	175 x 72 x 30 mm	257 x 160 x 37 mm
Manufacturer / Brand	ROGER	TP-LINK
Guarantee	3 years	2 years