

	FLUSH BOX 3-GANG PK-3X60/K-G/EPN Elektro-Plast	DUAL SMART CONTROLLER FOR ROLLER SHUTTERS ATLO-CW2-TUYA Wi-Fi, Tuya Smart	SMART SWITCH WITH TEMPERATURE AND HUMIDITY MEASUREMENT ATLO-TSH2-TUYA Wi-Fi, Tuya Smart
			
	8.77 PLN 8.77 PLN	76.25 PLN 76.25 PLN	96.05 PLN 96.05 PLN
Application	...	roller shutters, roof windows, awnings, drop-down screens, curtains	temperature and humidity measurement switching devices on/off
Number of sections	3
Power supply	...	100 ... 240 V AC, 50 / 60 Hz	90 ... 250 V
Temperature measurement	-40 °C ... 80 °C ± 0.5 °C
Material	Plastic
Measurement of humidity	0 % ... 99 % ± 3 %
Maximal total load	...	2 x 720 W	3750 W
Total maximal current	...	2 x 3 A	15 A
Number of inputs	...	4	1
Number of outputs	...	4	2
Montage hole diameter	3 x Ø 67 mm
Connector type	...	screw terminals + wires	screw terminals
Radio communication range	...	< 100 m (open area)	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi 2.4 GHz IEEE 802.11 b/g/n Bluetooth
Mobile phones support	...	<ul style="list-style-type: none"> The Tuya Smart free application on Android The Tuya Smart free application on iOS 	The Tuya Smart free application on Android The Tuya Smart free application on iOS
Manufacturer / Brand	Elektro-Plast
"Index of Protection"	—	IP20	...

Main features	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • 4 special screws with holders to fastening to the wall - included 	<ul style="list-style-type: none"> • Local control by physical button, • Możliwość użycia tylko przycisku monostabilnego, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control • Saving in the memory of the last adjustment of the position (from a button or application) 	<ul style="list-style-type: none"> • Warning indication about exceeding the preset temperature, • schedule, • timer, • remote access, • voice control, • Pairing button, • Wi-Fi indicator, • Temperature history graph, • For indoor use
Housing	...	Plastic	Plastic
Color	Brick red	White	White
Operation temp	...	-10 °C ... 40 °C	0 °C ... 40 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)
Weight	0.066 kg	0.042 kg	0.1 kg (total)
Dimensions	3 x Ø 60 x 47 mm - Internal dimensions 210 x 72 x 48 mm - External dimensions	<ul style="list-style-type: none"> • 43 x 39 x 22 mm • 10 cm (cable length) 	<ul style="list-style-type: none"> • 96 x 54 x 29 mm • 100 cm (cable length) Probe
Guarantee	2 years	2 years	2 years