

|                               | BLANK PANEL TO RACK<br>CABINET Z19-2U*P2  | MOUNT RACK FRAME<br>U19-4U/34Q  | IP CAMERA IPC-HFW1530S-0280B-S6.5 Mpx 2.8 mm DAHUA  | VOLTAGE DISTRIBUTION<br>PANEL A19-TS-35/PD-3U  | LEG LEVELER A19-N*P4 TO<br>RACK CABINET   |
|-------------------------------|---|---|---|--|---|
|                               |  |  |    |   |  |
|                               | 28.52 PLN<br>28.52 PLN  | 99.49 PLN<br>99.49 PLN  | 818.00 PLN<br>818.00 PLN  | 172.02 PLN<br>172.02 PLN   | 33.15 PLN<br>33.15 PLN  |
| Standard                      | ...   | ...   | TCP/IP  | ...  | ...   |
| Sensor                        | ...   | ...   | 1/2.7" Progressive Scan CMOS  | ...  | ...   |
| Matrix size                   | ...   | ...   | 5 Mpx   | ...  | ...   |
| Internal depth                | ...   | 330 mm  | ...   | ...  | ...   |
| In package                    | <b>2 pcs The price for package</b>  | ...   | ...   | ...  | <b>4 pcs The price for package</b>  |
| Width                         | 19"   | ...   | ...   | 19"  | Ø 39 mm   |
| Height                        | 2 U   | ...   | ...   | 3 U  | 100 mm  |
| Material                      | Steel - powder painted  | ...   | ...   | Steel - powder painted   | ...   |
| Application                   | ...   | ...   | ...   | RACK 19"   | ...   |
| Screw type                    | ...   | ...   | ...   | ...  | M12   |
| Max cabinet's weight          | ...   | ...   | ...   | ...  | 250 kg  |
| Main features                 | ...   | ...   | ...   | <ul style="list-style-type: none"> <li>• TH-35 rail</li> <li>• Corrosion resistance</li> <li>• Possibility to mount of 24 fuses, 1 S wide</li> <li>• 6-point fixing to the front RACK rails</li> <li>• 6 pcs. of M6 screws with cage nuts included</li> <li>• The enclosure features labeling field 420x20 mm</li> </ul> | ...   |
| Operation temp                | ...   | ...   | ...   | -10 °C ... 40 °C   | ...   |
| Resolution                    | ...   | ...   | 2880 x 1620 - 5 Mpx ,<br>2688 x 1520 - 4 Mpx ,<br>2560 x 1440 - 3.7 Mpx ,<br>2048 x 1536 - 3 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p<br>1280 x 960 - 1.3 Mpx<br>1280 x 720 - 720p                       | ...  | ...   |
| Lens                          | ...   | ...   | 2.8 mm  | ...  | ...   |
| View angle                    | ...   | ...   | <ul style="list-style-type: none"> <li>• 106° (manufacturer data)</li> <li>• 102 (our tests result)</li> </ul>  | ...  | ...   |
| Range of IR illumination      | ...   | ...   | 30 m  | ...  | ...   |
| RS-485 interface              | ...   | ...   | —   | ...  | ...   |
| Memory card slot              | ...   | ...   | —   | ...  | ...   |
| Image compression method      | ...   | ...   | H.265+ / H.265 / H.264 / H.264+ / MJPEG   | ...  | ...   |
| Alarm inputs / outputs        | ...   | ...   | —   | ...  | ...   |
| Audio                         | ...   | ...   | <ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>  | ...  | ...   |
| Main stream frame rate        | ...   | ...   | 20 fps @ 5 Mpx<br>25 fps @ 4 Mpx  | ...  | ...   |
| Network interface             | ...   | ...   | 10/100 Base-T (RJ-45)   | ...  | ...   |
| Network protocols             | ...   | ...   | IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, SMTP, FTP, DHCP, DNS, DDNS, NTP, Multicast   | ...  | ...   |
| WEB Server                    | ...   | ...   | Built-in  | ...  | ...   |
| Max. number of on-line users  | ...   | ...   | 6   | ...  | ...   |
| ONVIF                         | ...   | ...   | 20.06   | ...  | ...   |
| Mobile phones support         | ...   | ...   | <ul style="list-style-type: none"> <li>Port no.: 37777 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul> | ...  | ...   |
| Default IP address            | ...   | ...   | 192.168.1.108   | ...  | ...   |
| Default admin user / password | ...   | ...   | admin / -<br>The administrator password should be set at the first start  | ...  | ...   |
| Web browser access ports      | ...   | ...   | 80, 37777   | ...  | ...   |
| PC client access ports        | ...   | ...   | 37777   | ...  | ...   |
| Mobile client access ports    | ...   | ...   | 37777   | ...  | ...   |
| Port ONVIF                    | ...   | ...   | 80  | ...  | ...   |
| RTSP URL                      | ...   | ...   | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0<br>- Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1<br>- Sub stream                                 | ...  | ...   |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

|                       |         |   |   |   |         |
|-----------------------|---------|---|---|---|---------|
| Main features         | ...     | ...                                     | <ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Configurable Privacy Zones</li> <li>• Audio detection</li> <li>• Mirror - Mirror image</li> </ul> | ...   | ...     |
| Power supply          | ...     | ...                                     | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 330 mA</li> </ul>  | ...   | ...     |
| Power consumption     | ...     | ...                                     | <ul style="list-style-type: none"> <li>• ≤ 3.9 W @ 12 V DC</li> <li>• ≤ 4.5 W @ PoE (802.3af)</li> </ul>  | ...   | ...     |
| Housing               | ...     | ...                                     | Compact - Metal   | ...   | ...     |
| Color                 | Black   | Black (RAL 9005)                        | White   | Black (RAL 9005)  | ...     |
| "Index of Protection" | ...     | ...                                     | IP67  | IP20  | ...     |
| Operation temp        | ...     | ...                                     | -40 °C ... 60 °C  | ...   | ...     |
| Weight                | 0.37 kg | 2.71 kg                                 | 0.32 kg   | 2.06 kg   | 0.12 kg |
| Dimensions            | ...     | 500 x 151 x 331 mm -<br>RACK 19 " x 4 U | Ø 70 x 162 mm   | 445 x 125 x 55 mm Internal<br>dimensions<br>481 x 132 x 135 mm<br>External dimensions | ...     |
| Supported languages   | ...     | ...                                     | English, Spanish, Russian   | ...   | ...     |
| Manufacturer / Brand  | ...     | ...                                     | DAHUA   | PULSAR  | ...     |
| Guarantee             | 2 years | 2 years                                 | 3 years   | 2 years   | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00