



	ANTENNA AP-5/2.4	IP CAMERA DS-2CD2386G2-ISU/SL(2.8MM)(C)(BLACK) ACUSENSE - 8.3 Mpx Hikvision
		
	23.18 PLN 23.18 PLN	1927.00 PLN 1927.00 PLN
Standard	...	TCP/IP
Sensor	...	1/1.8 " Progressive Scan CMOS
Frequency range	2.4 GHz ... 2.5 GHz	...
Matrix size	...	8.3 Mpx
Impedance	50 Ω	...
Scanning system	...	Progressive
Gain	5 dBi ... 7 dBi	...
Connector	SMA-RP plug	...
Horizontal beam width (H)	360 °	...
Vertical beam width (V)	32 °	...
Resolution	...	3840 x 2160 - 8.3 Mpx , 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	• 111 ° (manufacturer data) • 106 ° (our tests result)
Range of IR illumination	...	30 m
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	1 / 1
Audio	...	• Microphone built-in • 1 Audio input • 1 Audio output • Speaker built-in - Alarm siren • Bi-directional audio streaming support
Main stream frame rate	...	25 fps @ 8.3 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, ARP
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	18.12

Main features	...	<ul style="list-style-type: none"> • Camera from AcuSense series • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Day/night mode • ICR - Movable InfraRed filter • WB - White Balance • AGC - Automatic Gain Control • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Mirror - Mirror image • Configurable Privacy Zones • Motion Detection • Filtering of false alarms based on the recognition of persons and vehicles • Light and sound alarm, • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection, advanced face capture features
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/- with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/- with authorization
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 750 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 10 W @ PoE (802.3af) • ≤ 9 W @ 12 V DC
Housing	...	Dome, Metal
Color	...	Black

"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	...	0.84 kg
Dimensions	...	Ø 138 x 125 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand	...	Hikvision
SAP Code	...	311316755
Guarantee	2 years	3 years

