

	LED AMPLIFIER AMPBOX/BLEBOX 12 ... 24 V DC	POE SWITCH / EXTENDER XPOE-3-11A 3-PORT ATTE
		
	72.40 PLN 72.40 PLN	185.00 PLN 185.00 PLN
LAN ports	...	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at) / Passive PoE, • 2 x RJ45 10/100 Base-T + Passive PoE
Management	...	—
Application	<ul style="list-style-type: none"> • Works with LED controllers : WLIGHTBOX-V3/BLEBOX, WLIGHTBOX-S-V2/BLEBOX, REFLECTIVE-SWITCH/BLEBOX, TWILIGHT-SWITCH/BLEBOX, PROXIDIMMER/BLEBOX, • Works with LED lighting - (RGB/RGBW/CCT/MONO) 12-24V LED strips 	...
LED diodes	...	LAN, PoE
Rated voltage	12 ... 24 V DC	...
Maximal total load	480 W	...
Transmission speed	...	10 / 100 Mbps : 1 Port LAN + 2 LAN & PoE ports
Maximal output power	...	50 W @ port PoE
Total maximal current	20 A (5 A / Channel)	...
Maximal total power	...	50 W
Number of inputs	4	...
Number of outputs	4	...
Connector type	screw terminals	...
Wireless	—	...
Mobile phones support	—	...
Power supply	...	<ul style="list-style-type: none"> • 35 ... 56 V DC - Passive PoE @ LAN 1 • 44 ... 56 V - PoE (802.3af/at) @ LAN 1
Power consumption	...	< 0.5 W

Main features	<ul style="list-style-type: none"> • High power - max. 480 W, • Digital signal enhancement, • Signal correction : digital, • Protections : optical isolation, • Powerful and high performance, • Small dimensions 	<ul style="list-style-type: none"> • Switch powered by PoE in accordance with the IEEE 802.3af/at standard or via Passive PoE from ATTE devices • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender • The output PoE voltage is equal to the input voltage • Sequential start of PoE OUT outputs
Housing	Plastic	...
"Index of Protection"	IP20	...
Color	Black	...
Operation temp	-20 °C ... 50 °C	...
Weight	0.036 kg	0.03 kg
Dimensions	48 x 39 x 18 mm	73 x 52 x 23 mm
Manufacturer / Brand	BleBox	ATTE
Guarantee	2 years	3 years