




	ACCESS CONTROL PANEL ACCO-NT SATEL	ACCESS CONTROL PANEL CPR32-SE-BRD ROGER	ELECTRIC CABLE YDY-5X6.0
			
	1558.00 PLN 1558.00 PLN	650.01 PLN 650.01 PLN	24.57 PLN 24.57 PLN
Inputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264 	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 32 	...
In section	100 m . Price for 1m when buying a whole roll
Inner conductor	5 x 6.0 mm ² - Cu wire
Rated voltage	450 / 750 V
Outputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264 	<ul style="list-style-type: none"> • 4 pcs - Transistor outputs • 2 pcs - Relay outputs NO/NC 	...
Outer coating	Ø 16.5 mm - PVC
Coating color	White
Communication	<ul style="list-style-type: none"> • 2 x RS-485 • Expander bus - up to 32 expander modules 	<ul style="list-style-type: none"> • RS-485, • RACS (Roger) 	...
Events memory	<ul style="list-style-type: none"> • Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module 	Non-volatile log buffer of the last 250 000 events	...
Users + admins	<ul style="list-style-type: none"> • 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Output load	<ul style="list-style-type: none"> • OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC 	<ul style="list-style-type: none"> • Transistor outputs : 1 A / 15 V DC • Relay outputs : REL1 - 1.5 A / 30 V DC REL2 - 5 A / 230 V AC 	...

Main features	<ul style="list-style-type: none"> • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses 	<ul style="list-style-type: none"> • Ability to block/unblock partition at a specified time, or as per access schedule, • Central management of the access control system, • Integration with the alarm system SATEL INTEGRA, • History of 250 000 events • Electrical protection of all inputs and outputs as well as communication buses • DIN, TS-35 rail mounting 	...
Power supply	12 V DC / 125 mA (max)	<ul style="list-style-type: none"> • 24 V DC • 12 V DC • 18 V AC 	...
Battery backup support	—	✓	...
Operation temp	-10 °C ... 55 °C	5 °C ... 40 °C	...
Permissible relative humidity	93 % (non-condensing)	10 % ... 95 % (non-condensing)	...
Dimensions	151 x 69 x 17 mm	105 x 85 x 50 mm	...
Weight	0.092 kg	0.12 kg	...
Manufacturer / Brand	SATEL	ROGER	...
Guarantee	2 years	3 years	2 years