



	<a href="#">PROJECTOR MOUNT PD-670</a>	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H51V21-28W 2Mpx / 5Mpx 2.8 mm</a>
		
	62.24 PLN 62.24 PLN	124.80 PLN 124.80 PLN
Bearing capacity	20 kg	...
Standard	...	AHD, HD-CVI, HD-TVI
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Distance from mounting surface	• 430 ... 650 mm (vertical), • 350 ... 560 mm (horizontal)	...
Projector mounting holes distances	Ø 225 ... 316 mm	...
Tilt adjustment	-15 ° ... 15 °	...
Horizontal rotation	-8 ° ... 8 °	...
Main features	Possibility to mount on the wall or ceiling	...
Material	Steel - powder painted	...
Resolution	...	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Range of IR illumination	...	20 m
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 mm
View angle	...	• 89 ° (manufacturer data) • 82 ° (our tests result)
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu	...	✓

Main features	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> <li>• Coaxial audio - HD-TVI only</li> </ul>
Housing	...	Dome - Metal
Color	Silver	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Power supply	...	12 V DC / 250 mA
Power consumption	...	≤ 3 W
Operation temp	...	-20 °C ... 60 °C
Weight	1.5 kg	0.42 kg
Dimensions	...	Ø 97 x 91 mm
Supported languages	...	Polish, English
Manufacturer / Brand	...	APTI
Guarantee	2 years	2 years