



	CONVERTER MODULE AVC-30-120-OF DC/DC ATTE	ACCESS POINT 4G LTE +ROUTER ARCHER-MR200 2.4 GHz, 5 GHz 433 Mbps + 300 Mbps TP-LINK
		
	23.60 EUR 23.60 EUR	84.61 EUR 84.61 EUR
Type	Decreasing and increasing the voltage, DC/DC	...
Frequency range	...	2.4 GHz , 5 GHz
Number of inputs	1	...
Number of outputs	1	...
Power voltage	6 ... 35 V DC	...
Output voltage	12 V DC	...
Antenna type	...	3 x WiFi - built-in , 2 x 4G LTE
Output voltage adjustment	—	...
Output current	2.5 A (max)	...
Power	30 W (max)	...
Standards	...	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3/3u
Protections	<ul style="list-style-type: none"> • Short-circuit (3 A) • Reverse polarity of the input voltage • Overvoltage 	...
Application	to recorder powering - 12 V	...
Baud rates	...	<ul style="list-style-type: none"> • 5 GHz : 433 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 150 Mbps
Modulation type	...	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM
LAN ports	...	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN

Receiver sensitivity	...	5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -67dBm • 11ac HT40: -64dBm • 11ac HT80: -60dBm • 11n HT20: -71dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -76dBm • 11n HT20: -73dBm • 11n HT40: -67dBm
LTE	...	✓
QSS	...	✓
WDS	...	✓
Power supply	...	12 V DC / 1 A (power adapter included)
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	95 % (non-condensing)
Main features	Efficiency : 90 % @ 12 V / 30 W	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button
Weight	0.03 kg	0.26 kg
Dimensions	39 x 61 x 22 mm	202 x 163 x 34 mm
Manufacturer / Brand	ATTE	TP-LINK
Guarantee	3 years	3 years