



	<a href="#">MULTI-PURPOSE AGENT K2-07/150ML SPRAY 150 ml K2</a>	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H51V21-36W 2Mpx / 5Mpx 3.6 mm</a>
		
	10.55 PLN 10.55 PLN	120.00 PLN 120.00 PLN
Package	Spray 150 ml	...
Standard	...	AHD, HD-CVI, HD-TVI
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Application	<ul style="list-style-type: none"> <li>• Elimination of squeaks,</li> <li>• Lubrication,</li> <li>• Removal of water,</li> <li>• Penetration,</li> <li>• Corrosion protection,</li> <li>• Surface preservation,</li> <li>• Removal of dirt</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Spray formulation with a straw for easy application in hard-to-reach places</li> <li>• Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places</li> <li>• It can be used in any position, even upside down</li> </ul>	...
Resolution	...	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Range of IR illumination	...	20 m
IR illuminator power adjustment	...	Automatic
Lens	...	3.6 mm
View angle	...	<ul style="list-style-type: none"> <li>• 77 ° (manufacturer data)</li> <li>• 70 ° (our tests result)</li> </ul>
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch

OSD menu	...	✓
Main features	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> <li>• Coaxial audio - HD-TVI only</li> </ul>
Housing	...	Dome - Metal
Color	...	White
Vandal-proof	...	—
"Index of Protection"	...	IP67
Power supply	...	12 V DC / 250 mA
Power consumption	...	≤ 3 W
Operation temp	...	-20 °C ... 60 °C
Weight	0.15 kg	0.42 kg
Dimensions	Ø 52 x 143 mm	Ø 97 x 91 mm
Supported languages	...	Polish, English
Manufacturer / Brand	K2	APTI
Guarantee	...	2 years