




	EXTENSION CABLE DC-2.1/5.5-WG-15M 15 m	ACCESS CONTROLLER PR102DR-BRD ROGER	UPS COVER-BASIC-1K 1000 VA COVER
			
	48.00 PLN 48.00 PLN	345.01 PLN 345.01 PLN	791.20 PLN 791.20 PLN
Environment class	...	I	...
Power adapter type	Online
Nominal power	900 W
Relay contacts load	...	1.5 A / 30 V	...
Apparent Power	1000 VA
Battery backup support	...	—	...
Input lines	...	2	...
Output lines	...	2	...
Connector type	1 x Ø 2.1/5.5 mm Straight socket 1 x Ø 2.1/5.5 mm Straight plug
Length of the cable	15 m
Input voltage	208 V / 220 V / 230 V / 240 V AC
Communication	...	<ul style="list-style-type: none"> • RS-485 • RACS (Roger) 	...
Rated voltage	12 V DC
Color	Black
Input frequency	50 / 60 Hz @ -20 % / +20 %
Power supply	...	10 ... 15 V DC	...
Output voltage	208 V / 220 V / 230 V / 240 V AC (Pure Sine Wave)
Operation temp	...	5 °C ... 40 °C	...
Power factor	0.9
Permissible relative humidity	...	10 ... 95 % (non-condensing)	...
Output frequency	50 / 60 Hz ± 0.05 Hz
Voltage adjustment	✓
Frequency adjustment	✓
Charging time (recover to 90% capacity)	4 hours
Battery	3 x 12V/9Ah
Estimated battery operation time	<ul style="list-style-type: none"> • 20 minutes @ 450 W, • 12 minutes @ 675 W, • 8 minutes @ 900 W
Number of outputs	8 pcs IEC-320 C13
Management software	ViewPower

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	<ul style="list-style-type: none"> • Short-circuit • Overload • Overcharge protection • discharge protection • Output voltage filtering • EPO (Emergency power off) switch
Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling
Main features	...	<ul style="list-style-type: none"> • PRT series readers support • 4000 indexed users • History of 32000 events • Real-time clock and calendar • Remote programming from PC 	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic bypass • The device has a rotating display • COLD START function for manual switch to the battery power supply • Battery charge and maintenance control • Port RS-232 - Access from PC • Remote management - ViewPower application (included) • Battery replacement during operation (Hot-swap) • Network card slot • Can be mounted in a Rack 19" cabinet
Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity	0 °C ... 45 °C / 0 ~ 95 % (non-condensing)
Weight	0.245 kg	0.04 kg	9.22 kg
Dimensions	...	80 x 54 x 18 mm	291 x 146 x 223 mm ; RACK 19", 2U
Manufacturer / Brand	...	ROGER	COVER
Guarantee	2 years	3 years	2 years