



	<a href="#">BATTERY PACK DS-PM1-D TO AX PRO CONTROL PANELS Hikvision</a>	<a href="#">COAXIAL CABLE TRI-LAN-400 50 Ω</a>
		
	134.00 PLN 134.00 PLN	11.60 PLN 11.60 PLN
Support	HIKVISION AX PRO	...
In section	...	<b>100 m . Price for 1m when buying a whole roll</b>
Inner conductor	...	Ø 2.7 mm Cu ± 0.02 mm Wire
Power supply	8 V ... 24 V DC	...
Dielectric	...	Ø 7.2 mm Physical foam
Operation temp	-10 °C ... 55 °C	...
Shield	...	Foil - Al/PET
Permissible relative humidity	10 % ... 90 %	...
Weight	0.03 kg	...
Braid	...	168 x Ø 0.15 mm Stranded wire CuSn
Dimensions	79 x 91 x 19 mm	...
Impedance	...	50 Ω
Manufacturer / Brand	Hikvision	...
SAP Code	302401878	...
Outer coating	...	Ø 10.3 mm ± 0.20 mm PE
Main features	<ul style="list-style-type: none"> <li>• Output voltage : 5.5 V DC - stabilized</li> <li>• Very easy and quick assembly</li> </ul>	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• it can be used in WLAN 2,4GHz and 5GHz installations</li> <li>• Operation temp : -40 °C ... 70 °C</li> </ul>

Cable attenuation at 100m section	...	Temperature : 20 °C 2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz
Maximum transmitted power	...	3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz
Guarantee	2 years	2 years

