



	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE56D8T-ITMF(2.8MM) - 1080p Hikvision	ACCESS POINT RG-RAP2260(E) Wi-Fi 6 2.4 GHz 5 GHz 574 Mbps + 2402 Mbps REYEE
		
	323.00 PLN 323.00 PLN	1150.00 PLN 1150.00 PLN
Standard	AHD / HD-CVI / HD-TVI / CVBS	...
Sensor	Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Frequency range	...	2.4 GHz (2.400 ... 2.4835 GHz) 5 GHz (5.150 ... 5.850 GHz)
Resolution	<ul style="list-style-type: none"> • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI • 960 x 576 - 960H @ PAL 	...
Antenna type	...	4x4 MU-MIMO, 2.4 GHz / 5.0 GHz - 3 dBi, Integrated - 5 x Omnidirectional antenna
Range of IR illumination	30 m	...
Standards	...	IEEE 802.11 a/b/g/n/ac/ax
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
Baud rates	...	574 Mbps + 2402 Mbps
View angle	<ul style="list-style-type: none"> • 104 ° (manufacturer data) • 101 ° (our tests result) 	...
IR illuminator support	ICR - Movable InfraRed filter	...
Wireless transmission range	...	40 m - 2.4 GHz 70 m - 5 GHz
S/N ratio	> 62 dB	...
Default IP address	...	10.44.77.254
Protections	...	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK
LAN ports	...	1 x 10/100/2500 Mbps 1 x 10/100/1000 Mbps
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...

Mobile phones support	...	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Transmitter power	...	≤ 31 dBm @ 2.4 GHz (max) ≤ 32.7 dBm @ 5.0 GHz (max)
Power supply PoE	...	PoE (802.3at)
Main features	<ul style="list-style-type: none"> • WDR ≥ 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines 	...
OSD menu	OSD menu available via recorder	...
Power supply	12 V DC / 280 mA	12 V / 2 A (power adapter not included)
Power consumption	≤ 3.4 W	≤ 18 W
Housing	Dome, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...

Main features	...	<ul style="list-style-type: none"> • Possibility to mount on the wall or ceiling • Support for Reye Mesh technology • Number of users : 512 (max) • OFDMA • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • WMM (Wi-Fi Multimedia) • Load balance • AP placement and RF maps • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions
Operation temp	-40 °C ... 60 °C	...
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	5 % ... 95 %
Weight	0.24 kg	1.1 kg
SAP Code	300612680	...
Dimensions	91 x 83 x 68 mm	220 x 220 x 48 mm
Manufacturer / Brand	Hikvision	RUIJIE / REYEE
Guarantee	3 years	3 years