



|                                  |   |  |
|----------------------------------|---|--|
|                                  | <a href="#">ROUTER WIFI N3 2.4 GHz<br/>300 Mbps DAHUA</a>   | <a href="#">AHD, HD-CVI, HD-TVI, PAL<br/>CAMERA HAC-HDW2802T-<br/>A-0280B - 8.3 Mpx, 4K UHD<br/>2.8 mm DAHUA</a> |
|                                  |    |                                |
|                                  | 55.00 PLN<br>55.00 PLN  | 779.00 PLN<br>779.00 PLN   |
| Frequency range                  | 2.4 GHz   | ...  |
| Antenna type                     | 2 x Omnidirectional antenna<br>- Integrated, 3 dBi  | ...  |
| Standard                         | ...   | AHD, HD-CVI, HD-TVI, PAL   |
| Sensor                           | ...   | 1/1.8 " Progressive Scan<br>CMOS   |
| Standards                        | IEEE 802.11 a/b/g/n   | ...  |
| Matrix size                      | ...   | 8.3 Mpx  |
| Baud rates                       | 300 Mbps  | ...  |
| LAN ports                        | 3 x 10/100 Mbps LAN<br>1 x 10/100 Mbps WAN  | ...  |
| LED indicators                   | Status  | ...  |
| DHCP server                      | ✓   | ...  |
| Firmware update                  | ✓   | ...  |
| Protections                      | WPA-PSK, WPA2-PSK   | ...  |
| Management interface             | Web browser   | ...  |
| Default admin user /<br>password | admin / admin123  | ...  |
| Transmitter power                | max. 20 dBm   | ...  |
| Main features                    | <ul style="list-style-type: none"> <li>• Static / dynamic routing</li> <li>• Built-in 3-port switch</li> <li>• DMZ</li> <li>• UPnP</li> <li>• DHCP client list</li> </ul> | ...  |
| Operation temp                   | -10 °C ... 40 °C  | ...  |
| Permissible relative<br>humidity | 10 % ... 90 % (non-<br>condensing)  | ...  |

|                                 |  |  |
|---------------------------------|--|--|
| Resolution                      | ...                                      | <ul style="list-style-type: none"> <li>• HD-CVI :<br/>3840 x 2160 - 8.3 Mpx, 4K UHD @ 15 fps ,<br/>3072 x 2048 - 6.3 @ 20 fps ,</li> <li>• 2560 x 1440 - 3.7 Mpx @ 25 fps ,</li> <li>• AHD / HD-TVI :<br/>2592 x 1944 - 5 Mpx ,<br/>2560 x 1440 - 3.7 Mpx @ 25 fps ,</li> <li>• CVBS :<br/>960 x 576 - 960H, PAL</li> </ul>                              |
| IR illuminator support          | ...                                      | ICR - Movable InfraRed filter  |
| Range of IR illumination        | ...                                      | 50 m   |
| IR illuminator power adjustment | ...                                      | Automatic  |
| S/N ratio                       | ...                                      | > 65 dB  |
| Lens                            | ...                                      | 2.8 mm   |
| View angle                      | ...                                      | <ul style="list-style-type: none"> <li>• 111 ° (manufacturer data)</li> <li>• 106 ° (our tests result)</li> </ul>  |
| Video output                    | ...                                      | AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω  |
| Audio                           | ...                                      | <ul style="list-style-type: none"> <li>• Microphone built-in - HD-CVI only,</li> <li>• External microphone input - HD-CVI only</li> </ul>  |
| Main features                   | ...                                      | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> </ul> |
| OSD menu                        | ...                                      | OSD menu available via DAHUA recorder  |
| Power supply                    | 12 V DC / 0.5 A (power adapter included) | 12 V DC / 670 mA   |
| Power consumption               | ≤ 3.2 W                                  | ≤ 8 W  |
| Housing                         | ...                                      | Dome, Aluminum   |
| Color                           | ...                                      | White  |
| Vandal-proof                    | ...                                      | —  |

|                       |                    |  |
|-----------------------|--------------------|--|
| "Index of Protection" | ...                | IP67   |
| Operation temp        | ...                | -30 °C ... 60 °C   |
| Weight                | 0.13 kg            | 0.51 kg  |
| Dimensions            | 152 x 150 x 125 mm | Ø 106 x 99 mm  |
| Supported languages   | ...                | Polish, English, French,<br>Spanish, German,<br>Portuguese, Russian, Italian |
| Manufacturer / Brand  | DAHUA              | DAHUA  |
| Guarantee             | 2 years            | 3 years  |