




	AHD, HD-CVI, HD-TVI CAMERA APTI-H51V2-36 2Mpx / 5Mpx 3.6 mm	IP CAMERA IPC2314LE-ADF28KM-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW
		
	120.00 PLN 120.00 PLN	945.15 PLN 945.15 PLN
Standard	AHD, HD-CVI, HD-TVI	TCP/IP
Sensor	1/3 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS
Matrix size	5 Mpx	4 Mpx
White light LED illuminator range	...	30 m
S/N ratio	...	> 52 dB
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Resolution	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
WEB Server	...	Built-in
Range of IR illumination	20 m	...
Max. number of on-line users	...	32
IR illuminator power adjustment	Automatic	...
ONVIF	...	✓
Lens	3.6 mm	2.8 mm
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
View angle	<ul style="list-style-type: none"> • 77 ° (manufacturer data) • 70 ° (our tests result) 	<ul style="list-style-type: none"> • 110 ° (manufacturer data) • 106 ° (our tests result)

Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	...
OSD menu	✓	...
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only 	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette)
Power supply	12 V DC / 230 mA	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA
Power consumption	≤ 2.8 W	≤ 5.9 W
Housing	Dome - Metal	Compact, Metal
Color	Graphite	White
"Index of Protection"	IP67	IP67

Vandal-proof	—	—
Operation temp	-20 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.42 kg	0.41 kg
Dimensions	Ø 96 x 91 mm	206 x 73 x 37 mm
Supported languages	Polish, English	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	APTI	UNIVIEW
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00