



	NVR TC-R3440 SPEC:I/B/N/V4.0 40 CHANNELS TIANDY	EXTENDER HDMI-EX-4
		
	4200.00 PLN 4200.00 PLN	200.00 PLN 200.00 PLN
Standard	IP	...
Supported resolutions	max. 16 Mpx	...
Video outputs	1 pcs HDMI 4K 1 pcs VGA Video outputs are independent of each other	...
Audio support	40 Channels - Audio from cameras	...
Supported HDMI resolutions	...	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Audio inputs	1 pcs	...
Audio outputs	1 pcs	...
Image compression method	S+265 / H.265 / S+264 / H.264	...
Supported hard drives	4 x 10 TB SATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Maximal transmission range	...	<ul style="list-style-type: none"> • 40 m @ 720p / 1080p - UTP cat. 6 (manufacturer data) • 60 m @ 1080p - UTP cat. 6 (our tests result) • 50 m @ 1080p - UTP cat. 5e (our tests result)
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Playback max. 16 cameras in the same time 	...
Supported audio formats	...	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD
Operation temp	...	-10 °C ... 55 °C
Network interface	2 x RJ-45 - 10 / 100 / 1000 Mbps	...
Permissible relative humidity	...	5 % ... 90 %
Network functions	Full support via network, Remote records copying, Web-Server built-in	...
ONVIF	✓	...
Bitrate	max. 400 Mbps	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel.:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.3	...
RTSP URL	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
PC client access ports	3000, 3001	...
Mobile client access ports	3000, 3001	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Alarm inputs / outputs	16 / 4	...
Motion Detection	✓	...
Intelligent image analysis	—	...
USB	1 x USB 2.0 + 1 x USB 3.0	...
RS232	1 pcs	...
RS485	1 pcs	...
Mouse support	✓	...
IR remote controller in the set	—	...

Main features	<ul style="list-style-type: none"> • Possibility of operation the disks in RAID JBOD/0/1/5/6/10 array Support for Intelligent Image Analysis function, available in TIANDY cameras : <ul style="list-style-type: none"> • crossing the line (tripwire) • double crossing the line • abandoned/missing object • detection of loitering in a given area • running • parking detection • heat map • scene changing • signal loss indication • License plate recognition • detection of persons on duty • detection of people gathering • Parking monitoring mode • protective helmet detection • people counting • advanced face capture features - (max 100 000 faces in the database) 	...
Power supply	12 V DC / 5 A (power adapter included)	5 V DC / 1000 mA - 2 pcs of power adapters included
Weight	3.32 kg	0.045 kg
Dimensions	440 x 355 x 76 mm	67 x 56 x 22 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Vietnamese, German, Ukrainian, Portuguese	...
Manufacturer / Brand	TIANDY	...
Guarantee	3 years	2 years